

Adapter cable - CABLE-15/8/250/RSM/PD - 2981758

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Cable adapter for PSR speed monitors (PSR-RSM4 and PSR-MOTIONSTOP), 15/8-pos., cable length: 2.5 m, for controller: Parker Drives



Product Features

- ✓ Option to connect to PSR-RSM4 and PSR-MOTIONSTOP safe speed monitors
- ✓ Suitable for connection to the existing motor feedback interface of an electrical drive
- ✓ Controller type: PARKER Drives
- ✓ 15-pos. D-SUB connection
- ✓ Length of connecting cable to speed monitor: 250 cm

Key commercial data

Packing unit	1 PCE
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Fixed cable length	2.5 m
--------------------	-------

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C (for fixed installation)
	0 °C ... 50 °C (for flexible installation)
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Connection 1	To the device
Connection method	RJ45
	D-SUB-15 male/D-SUB-15 female
Number of positions	15
Cable resistance	≤ 260 Ω/km
Conductor material	Bare Cu litz wires

Adapter cable - CABLE-15/8/250/RSM/PD - 2981758

Technical data

General

Shielding	Plastic-coated aluminum foil, tinned copper braided shield
	Soldering on D-SUB housing
Conductor cross section	0.48 mm ² (AWG 26)

Classifications

eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371901
eCl@ss 5.1	27371901
eCl@ss 6.0	27060307
eCl@ss 7.0	27060307
eCl@ss 8.0	27060307

ETIM

ETIM 2.0	EC001449
ETIM 3.0	EC001449
ETIM 4.0	EC000467
ETIM 5.0	EC000830

UNSPSC

UNSPSC 6.01	30211901
UNSPSC 7.0901	39121501
UNSPSC 11	39121501
UNSPSC 12.01	39121501
UNSPSC 13.2	39121501

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)