

# Label - MM-EML (15X9)R C1 YE/BK - 1116199

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Label, Roll, yellow/black, unlabeled, can be labeled with: THERMOMARK GO, mounting type: adhesive, lettering field size: 15 x 9 mm, Number of individual labels: 285

# **Product Description**

The MM-EML... polyester self-adhesive labels are available as pre-punched material for equipment marking.

#### Your advantages

- The pre-punched geometry enables easy and convenient use
- Thanks to the innovative material composition, each label can be printed which results in zero wastage
- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- In the second second

The pre-punched self-adhesive labels are particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing

- The material is cUL certified
- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing

# RoHS

# Key Commercial Data

Packing unit	1 pc
GTIN	4 063151 042035
GTIN	4063151042035
Custom tariff number	96121010
Country of origin	China

# **Technical data**

### Dimensions

Length (b)	9 mm
------------	------

06/09/2021 Page 1 / 3



# Label - MM-EML (15X9)R C1 YE/BK - 1116199

# Technical data

### Dimensions

Width (a)	15 mm	
Ambient conditions		
Ambient temperature (operation)	-40 °C 150 °C	
	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.	

### General

Color	yellow/black
Components	free from silicone, halogen, and cadmium
Material	Polyester
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	285
Marking mounting type	adhesive

# **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Classifications

## eCl@ss

eCl@ss 9.0	27400629
Approvals	

Approvals

Approvals

cULus Recognized

## Ex Approvals

## Approval details



http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

MH48542

06/09/2021 Page 2 / 3



Phoenix Contact 2021 © - all rights reserved http://www.phoenixcontact.com

06/09/2021 Page 3 / 3

>>Phoenix Contact(菲尼克斯)