

## Marshalling panel - PTRV 4 /COL-WH - 3001871

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Marshalling panel, Nom. voltage: 250 V, Nominal current: 10 A, Cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 12 - 26, Connection type: Push-in connection, Width: 8.3 mm, Length: 64 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

The figure shows a version of the article

### Product Features

- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Individual color assignment of cable and terminal point to ensure error-free, safe operation
- Color configuration possible according to VDE 0812, VDE 0815, DIN 47100 or unlimited.
- Tool-free wiring in a confined space thanks to compact size
- The 2.3 mm test connection enables testing between the conductors with test pins commonly used in the industry



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85369010 |
| Country of origin    | Poland   |

### Technical data

#### General

|                                        |                     |
|----------------------------------------|---------------------|
| Number of levels                       | 4                   |
| Number of connections                  | 16                  |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Color                                  | gray                |
| Insulating material                    | PA                  |
| Flammability rating according to UL 94 | V0                  |
| Rated surge voltage                    | 6 kV                |
| Overvoltage category                   | III                 |
| Insulating material group              | I                   |

# Marshalling panel - PTRV 4 /COL-WH - 3001871

## Technical data

### General

|                                |                                                         |
|--------------------------------|---------------------------------------------------------|
| Maximum load current           | 10 A (with 1.5 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub> | 10 A                                                    |
| Nominal voltage U <sub>N</sub> | 250 V                                                   |
| Open side panel                | Yes                                                     |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 8.3 mm  |
| Length           | 64 mm   |
| Height NS 35/7,5 | 55.5 mm |
| Height NS 35/15  | 63 mm   |

### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Connection method                                                          | Push-in connection   |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                           | 26                   |
| Conductor cross section AWG max.                                           | 12                   |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible                                 | 26                   |
| Max. AWG conductor cross section, flexible                                 | 14                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 1.5 mm <sup>2</sup>  |
| Stripping length                                                           | 8 mm ... 10 mm       |

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141121 |
| eCl@ss 4.1 | 27141121 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |

## Marshalling panel - PTRV 4 /COL-WH - 3001871

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

|                                |       |
|--------------------------------|-------|
| UL Recognized                  |       |
|                                | D     |
| mm <sup>2</sup> /AWG/kcmil     | 26-14 |
| Nominal current I <sub>N</sub> | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V |




# Marshalling panel - PTRV 4 /COL-WH - 3001871

## Approvals

|                                |       |
|--------------------------------|-------|
| cUL Recognized                 |       |
|                                | D     |
| mm²/AWG/kcmil                  | 26-14 |
| Nominal current I <sub>N</sub> | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V |

## Drawings

Circuit diagram



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)