

## Output module - UM-2KS50/DO 8/RS/KDS-3/SO227 - 2319168

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



8-channel digital output module with screw connection and integrated knife disconnect function. Redundant voltage supply with signaling relay. Suitable for Yokogawa SDV 531 card.

### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85369010 |
| Country of origin    | Germany  |

### Technical data

#### Note

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

#### Dimensions

|        |        |
|--------|--------|
| Width  | 145 mm |
| Height | 111 mm |
| Depth  | 98 mm  |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -20 °C ... 70 °C |
|---------------------------------|------------------|

#### General

|                                           |                                                          |
|-------------------------------------------|----------------------------------------------------------|
| Nominal voltage $U_N$                     | 30 V DC                                                  |
| Max. current carrying capacity per branch | 630 mA                                                   |
| Max. total current of voltage supply      | 6.3 A                                                    |
| Mounting position                         | any                                                      |
| Standards/specifications                  | Air and creepage distances DIN EN 50178 basic insulation |
| Pollution degree                          | 2                                                        |
| Surge voltage category                    | II                                                       |
| Rated surge voltage                       | 0.5 kV                                                   |
| Rated insulation voltage                  | 50 V                                                     |

## Output module - UM-2KS50/DO 8/RS/KDS-3/SO227 - 2319168

### Technical data

#### Connection data for connection 1

|                                        |                     |
|----------------------------------------|---------------------|
| Connection name                        | Field level         |
| Connection method                      | Screw connection    |
| Number of positions                    | 16                  |
| Conductor cross section solid min.     | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.     | 4 mm <sup>2</sup>   |
| Conductor cross section stranded min.  | 0.2 mm <sup>2</sup> |
| Conductor cross section stranded max.  | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG/kcmil min. | 24                  |
| Conductor cross section AWG/kcmil max  | 12                  |

#### Connection data for connection 2

|                       |                        |
|-----------------------|------------------------|
| Connection name       | Control system level   |
| Number of connections | 2                      |
| Connection method     | Yokogawa KS-compatible |
| Number of positions   | 50                     |

#### Supported controller

|                     |                     |
|---------------------|---------------------|
| Controller          | YOKOGAWA ProSafe-RS |
| - suitable I/O card | SDV531/-L           |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27069203 |
| eCl@ss 7.0 | 27069203 |
| eCl@ss 8.0 | 27069203 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001434 |
| ETIM 3.0 | EC001604 |
| ETIM 4.0 | EC001437 |
| ETIM 5.0 | EC001437 |

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 6.01 | 30211824 |
|-------------|----------|

## Output module - UM-2KS50/DO 8/RS/KDS-3/SO227 - 2319168

### Classifications

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11     | 39121421 |
| UNSPSC 12.01  | 39121421 |
| UNSPSC 13.2   | 39121421 |

Phoenix Contact 2014 © - all rights reserved  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)