

## BCH-500HS- 3 BK VPE500 - 5441605

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 12 A, Color: black, Contact surface: Tin, Mounting: Wave soldering



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 500 pc   |
| Weight per Piece (excluding packing) | 1.24 g   |
| Custom tariff number                 | 85366990 |
| Country of origin                    | China    |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

### Approvals

#### Approvals

#### Approvals

VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

## BCH-500HS- 3 BK VPE500 - 5441605

### Approvals

Approvals submitted

#### Approval details

VDE Gutachten mit Fertigungsüberwachung 

IECEE CB Scheme 

UL Recognized 

|                                | B     | D     |
|--------------------------------|-------|-------|
| Nominal current I <sub>N</sub> | 15 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

cUL Recognized 

|                                | B     | D     |
|--------------------------------|-------|-------|
| Nominal current I <sub>N</sub> | 15 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

cULus Recognized 

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)