

# Housing - HC-EVO-B06-SHWSC-2SSM32-PLRBK - 1407624

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

HEAVYCON EVO box mounting base, plastic, B6, with single locking latch, height 74 mm, with gland, 2 x M32, one of the two openings for the screw connections is sealed but can be broken open using a screwdriver, with protective cover.

## **Product Features**

- ☑ Lower costs than metal version
- ☑ Low weight
- ☑ Lower risk of condensation
- M Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Halogen-free plastic
- Impact test according to IK 08



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	160.0 GRM
Custom tariff number	85389099
Country of origin	Poland

## Technical data

## Dimensions

Height	74 mm
Width	57 mm
Length	84 mm

## Ambient conditions

Degree of protection of housing (IP)	IP66
	IP68 (0.2 bar 24 h)



# Housing - HC-EVO-B06-SHWSC-2SSM32-PLRBK - 1407624

# Technical data

#### Ambient conditions

	IP69K
Degree of protection of housing (NEMA)	4 (UL50e / NEMA 250)
	4X (UL50e / NEMA 250)
	12 (UL50e / NEMA 250)
Ambient temperature (operation)	-40 °C 125 °C (static)

#### General

Note	For contact inserts HC-B6, BB10, DD24, M.
Design	B6
Housing type	Box mounting bases
Color	black
Locking type	With single locking latch
No. of cable exits	2
Cable exit	Lateral
Screw connection	None
Type of the screw connection	2x M32
Protective cover	Yes
Housing material	Polyamide
Seal material	NBR
Material lock	Polyamide
Material, protective cover	Polyamide
Inflammability class according to UL 94	V0
Connection	One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.

# Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

ETIM

ETIM 3.0	EC000437

1/30/14 Page 2 / 3



# Housing - HC-EVO-B06-SHWSC-2SSM32-PLRBK - 1407624

# Classifications

ETIM


ETIM 4.0	EC000437
ETIM 5.0	EC000437

#### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Drawings





Dimensional drawing

 $\ensuremath{\mathbb{C}}$  Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com

>>Phoenix Contact(菲尼克斯)