


Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 41 A, connection method: Screw connection, Rated cross section: 6 mm², cross section: 0.2 mm² - 10 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Your advantages

- All universal terminal blocks in the UK... series can also be used in the Ex e area according to IEC/EN 60079 as standard
- The corresponding EC-type examination numbers for Ex approval can be found in the technical connection data

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Commercial Data

Item number	3004524
Packing unit	50 pc
Minimum order quantity	1 pc
Product Key	BE1211
Catalog Page	Page 460 (C-1-2019)
GTIN	4017918090821
Weight per Piece (including packing)	13.479 g
Weight per Piece (excluding packing)	13.014 g
Customs tariff number	85369010
Country of origin	CN

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Technical Data

Product properties

Product type	Feed-through terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	2
Nominal cross section	6 mm ²

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	10 mm
Internal cylindrical gage	A5
Conductor cross section solid	0.2 mm ² ... 10 mm ²
Cross section AWG	24 ... 8
Conductor cross section flexible	0.2 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	24 ... 12
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	0.25 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 6 mm ²
Cross-section with insertion bridge, rigid	4 mm ²
Cross-section with insertion bridge, flexible	4 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 1.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 4 mm ²
Nominal current	41 A
Maximum load current	57 A (with 10 mm ² conductor cross section)
Nominal voltage	800 V
Nominal cross section	6 mm ²

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Ex data

Rated data (ATEX/IECEX)

ATEX certificate	KEMA 98 ATEX 1651 U
IEC Ex certificate	IECEX KEM 06.0034 U
Identification	Ex eb IIC Gb
Operating temperature range	-60 °C ... 110 °C
Ex-certified accessories	3003020 D-UK 4/10
	3006027 D-UK 16
	3003224 ATP-UK
	1205066 SZS 1,0X4,0 VDE
	1201442 E/UK
Bridge data	37.5 A / 6 mm ²
	39.5 A / 6 mm ²
Ex temperature increase	40 K (47 A / 6 mm ²)
Rated voltage	630 V
for bridging with bridge	690 V
Rated insulation voltage	630 V

Ex level General

Rated current	41 A
Maximum load current	51 A
Contact resistance	0.16 mΩ

Ex connection data General

Torque range	1.5 Nm ... 1.8 Nm
Nominal cross section	6 mm ²
Rated cross section AWG	10
Connection capacity rigid	0.2 mm ² ... 10 mm ²
Connection capacity AWG	24 ... 8
Connection capacity flexible	0.2 mm ² ... 6 mm ²
Connection capacity AWG	24 ... 10
2 conductors with same cross section, solid	0.2 mm ² ... 1.5 mm ²
2 conductors with the same cross-section AWG rigid	24 ... 16
2 conductors with same cross section, stranded	0.2 mm ² ... 1.5 mm ²
2 conductors with the same cross-section AWG flexible	24 ... 16

Dimensions

Width	8.2 mm
End cover width	1.8 mm
Height NS 35/15	54.5 mm
Height NS 35/7,5	47 mm
Height	1.85 "
Height NS 32	52 mm
Length	42.5 mm

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 6 mm ²	0.72 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	5 N

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Result	Test passed
--------	-------------

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Drawings

Circuit diagram



Feed-through terminal block - UK 6 N



3004524


<https://www.phoenixcontact.com/pc/products/3004524>

Approvals

 DNV Approval ID: TAE00001CT				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
			-	-

 CSA Approval ID: 13631				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	600 V	50 A	26 - 8	-

 IECEE CB Scheme Approval ID: NL-65053				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	800 V	41 A	-	- 6

 cULus Recognized Approval ID: E60425				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	600 V	50 A	26 - 8	-
Multi-conductor connection	600 V	50 A	18 - 12	-
Use group C				
	600 V	50 A	26 - 8	-
Multi-conductor connection	600 V	50 A	18 - 12	-
Use group F				
	800 V	50 A	26 - 8	-
Multi-conductor connection	800 V	50 A	18 - 12	-

 KEMA-KEUR Approval ID: 71-119849				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	800 V	41 A	-	- 6

 LR Approval ID: 96/20013				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	800 V	41 A	-	- 6

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>



KR
Approval ID: HMB17372-EL001



NK
Approval ID: 09 ME 141

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
			-	-



RS
Approval ID: 17.00013.272



ATEX
Approval ID: KEMA98ATEX1651U



cUL Recognized
Approval ID: E192998

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	600 V	50 A	26 - 8	-



EAC Ex
Approval ID: RU C-DE.HA91.B.00066



GL
Approval ID: 98876-96 HH

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
EEx e II part certificate	690 V	43.5 A	-	- 6



IECEX
Approval ID: IECEX KEM 06.0034U



UL Recognized
Approval ID: E192998

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	600 V	50 A	26 - 8	-



CCC

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Approval ID: 2020322313000623



NEPSI

Approval ID: GYJ20.1195U



DNV GL-EX

Approval ID: TAE00003K6

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
EEx e II part certificate	440 V	32 A	-	- 2.5

cULus Recognized

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Classifications

ECLASS

ECLASS-9.0	27141120
ECLASS-10.0.1	27141120
ECLASS-11.0	27141120

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Accessories

 Note: Applying some accessories below might limit this product.

Partition plate

Partition plate - ATP-UK - 3003224

<https://www.phoenixcontact.com/pc/products/3003224>



Partition plate, length: 56 mm, width: 1.5 mm, height: 45.7 mm, color: gray

Screwdriver

Screwdriver - SZS 1,0X4,0 VDE - 1205066

<https://www.phoenixcontact.com/pc/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Switching jumper

Switching jumper - SB 2- 8/13 N - 0200062

<https://www.phoenixcontact.com/pc/products/0200062>



Switching jumper, pitch: 13 mm, color: silver

 Max. current carrying capacity: 40 A

Short-circuit connector

Short-circuit connector - KSS 8 - 0311540

<https://www.phoenixcontact.com/pc/products/0311540>



Short-circuit connector, pitch: 8 mm, color: black

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Fixed bridge

Fixed bridge - FBI 2- 8 - 0200020

<https://www.phoenixcontact.com/pc/products/0200020>



Fixed bridge, pitch: 8 mm, color: silver

 Max. current carrying capacity: 57 A


Fixed bridge

Fixed bridge - FBI 3- 8 - 0200059

<https://www.phoenixcontact.com/pc/products/0200059>



Fixed bridge, pitch: 8 mm, color: silver

 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>




Fixed bridge

Fixed bridge - FBI 4- 8 - 0200046

<https://www.phoenixcontact.com/pc/products/0200046>

Fixed bridge, pitch: 8 mm, color: silver



 Max. current carrying capacity: 57 A


Fixed bridge

Fixed bridge - FBI 10- 8 - 0203263

<https://www.phoenixcontact.com/pc/products/0203263>

Fixed bridge, pitch: 8 mm, color: silver



 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>




Fixed bridge

Fixed bridge - FBI 10- 8-EX - 0711700

<https://www.phoenixcontact.com/pc/products/0711700>

Fixed bridge, pitch: 8 mm, color: silver



 Max. current carrying capacity: 57 A


Fixed bridge

Fixed bridge - FB 2- 8-EX - 3029224

<https://www.phoenixcontact.com/pc/products/3029224>

Fixed bridge, pitch: 8 mm, color: silver



 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>




Fixed bridge

Fixed bridge - FB 4- 8 - 0202183

<https://www.phoenixcontact.com/pc/products/0202183>



Fixed bridge, color: silver

 Max. current carrying capacity: 57 A


Fixed bridge

Fixed bridge - FB 10- 8 - 0202170

<https://www.phoenixcontact.com/pc/products/0202170>



Fixed bridge, pitch: 8 mm, color: silver

 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Fixed bridge

Fixed bridge - FB 10- 8-EX - 3003185

<https://www.phoenixcontact.com/pc/products/3003185>

Fixed bridge, pitch: 8 mm, color: silver




 Max. current carrying capacity: 57 A

Zack marker strip

Zack marker strip - ZB 8:UNBEDRUCKT - 1052002

<https://www.phoenixcontact.com/pc/products/1052002>

Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snap in, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10



Feed-through terminal block - UK 6 N


3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Zack marker strip

Zack marker strip - ZB 8 CUS - 0825011

<https://www.phoenixcontact.com/pc/products/0825011>




Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Zack marker strip

Zack marker strip - ZB 8,LGS:FORTL.ZAHLEN - 1052015

<https://www.phoenixcontact.com/pc/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Zack marker strip

Zack marker strip - ZB 8,QR:FORTL.ZAHLEN - 1052028

<https://www.phoenixcontact.com/pc/products/1052028>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

DIN rail perforated

DIN rail perforated - NS 32 PERF 2000MM-VPE 10 - 1201002

<https://www.phoenixcontact.com/pc/products/1201002>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail perforated

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Insertion bridge

Insertion bridge - EB 2- 8 - 0202154

<https://www.phoenixcontact.com/pc/products/0202154>




Insertion bridge, pitch: 8 mm, color: gray

 Max. current carrying capacity: 57 A

Insertion bridge

Insertion bridge - EB 3- 8 - 0202141

<https://www.phoenixcontact.com/pc/products/0202141>



Insertion bridge, pitch: 8 mm, color: gray

 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>




Insertion bridge

Insertion bridge - EB 4- 8 - 0202142

<https://www.phoenixcontact.com/pc/products/0202142>

Insertion bridge, pitch: 8 mm, color: gray




 Max. current carrying capacity: 57 A


Insertion bridge

Insertion bridge - EB 10- 8 - 0202138

<https://www.phoenixcontact.com/pc/products/0202138>

Insertion bridge, pitch: 8 mm, color: gray



 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524


<https://www.phoenixcontact.com/pc/products/3004524>

Insertion bridge

Insertion bridge - EB 1/3/5/7-8 - 3072340

<https://www.phoenixcontact.com/pc/products/3072340>

Insertion bridge, pitch: 16.4 mm, pin assignment: 1, 3, 5, 7, color: gray



 Max. current carrying capacity: 57 A


Insertion bridge

Insertion bridge - EB 1/3/5-8 - 3072341

<https://www.phoenixcontact.com/pc/products/3072341>

Insertion bridge, pitch: 16.4 mm, pin assignment: 1,3,5, color: gray



 Max. current carrying capacity: 57 A

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Bridge bar isolator

Bridge bar isolator - IS-K 10 - 1303337

<https://www.phoenixcontact.com/pc/products/1303337>



Bridge bar isolator, color: gray

Cover

Cover - EA 5-WS - 1024085

<https://www.phoenixcontact.com/pc/products/1024085>



Single covers, for covering one terminal block, with black symbol (lightning flash)
snap fit, color: transparent/yellow

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Cover

Cover - EA 5 - 1024014

<https://www.phoenixcontact.com/pc/products/1024014>

Cover, material: ABS, color: transparent



End clamp

End clamp - CLIPFIX 35 - 3022218

<https://www.phoenixcontact.com/pc/products/3022218>

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

End clamp

End clamp - CLIPFIX 35-5 - 3022276

<https://www.phoenixcontact.com/pc/products/3022276>




Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

End clamp

End clamp - E/NS 35 N - 0800886

<https://www.phoenixcontact.com/pc/products/0800886>



End clamp, width: 9.5 mm, color: gray

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

End clamp

End clamp - E/UK - 1201442

<https://www.phoenixcontact.com/pc/products/1201442>

End clamp, material: PA, color: gray, Mounting on a DIN rail NS 32 or NS 35



End clamp

End clamp - E/UK 1 - 1201413

<https://www.phoenixcontact.com/pc/products/1201413>

End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray



Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Separating plate

Separating plate - TS-K - 1302215

<https://www.phoenixcontact.com/pc/products/1302215>



Separating plate, length: 22 mm, width: 0.5 mm, height: 22 mm, color: gray

End cover

End cover - D-UK 4/10 - 3003020

<https://www.phoenixcontact.com/pc/products/3003020>



End cover, length: 42.5 mm, width: 1.8 mm, height: 35.9 mm, color: gray

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Insulating sleeve

Insulating sleeve - PS-IH WH - 0311566

<https://www.phoenixcontact.com/pc/products/0311566>



Insulating sleeve, color: white

Insulating sleeve

Insulating sleeve - PS-IH RD - 0311579

<https://www.phoenixcontact.com/pc/products/0311579>



Insulating sleeve, color: red

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Insulating sleeve

Insulating sleeve - PS-IH BU - 0311582

<https://www.phoenixcontact.com/pc/products/0311582>



Insulating sleeve, color: blue

Insulating sleeve

Insulating sleeve - PS-IH YE - 0311595

<https://www.phoenixcontact.com/pc/products/0311595>



Insulating sleeve, color: yellow

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Insulating sleeve

Insulating sleeve - PS-IH GN - 0311605

<https://www.phoenixcontact.com/pc/products/0311605>



Insulating sleeve, color: green

Insulating sleeve

Insulating sleeve - PS-IH GY - 0311621

<https://www.phoenixcontact.com/pc/products/0311621>



Insulating sleeve, color: gray

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Insulating sleeve

Insulating sleeve - PS-IH BK - 0311634

<https://www.phoenixcontact.com/pc/products/0311634>



Insulating sleeve, color: black

Insulating sleeve

Insulating sleeve - PS-IH VT - 0311618

<https://www.phoenixcontact.com/pc/products/0311618>



Insulating sleeve, color: violet

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

End cap

End cap - NS 35/ 7,5 CAP - 1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



End cap

End cap - NS 35/15 CAP - 1206573

<https://www.phoenixcontact.com/pc/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 32 UNPERF 2000MM-VPE 10 - 1201015

<https://www.phoenixcontact.com/pc/products/1201015>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - 1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - 0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 WH UNPERF 2000MM-VPE 10 - 1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM-VPE 10 - 1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM-VPE 10 - 1201798

<https://www.phoenixcontact.com/pc/products/1201798>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver, Pack of 10 (20 m)

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Female test connector

Female test connector - PSBJ 4/15/6 FARBLOS - 0303419

<https://www.phoenixcontact.com/pc/products/0303419>



Female test connector, color: transparent

Female test connector

Female test connector - PSBJ 4/15/6 WH - 0303312

<https://www.phoenixcontact.com/pc/products/0303312>



Female test connector, color: white

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Female test connector

Female test connector - PSBJ 4/15/6 RD - 0303325

<https://www.phoenixcontact.com/pc/products/0303325>



Female test connector, color: red

Female test connector

Female test connector - PSBJ 4/15/6 BU - 0303354

<https://www.phoenixcontact.com/pc/products/0303354>



Female test connector, color: blue

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Female test connector

Female test connector - PSBJ 4/15/6 YE - 0303367

<https://www.phoenixcontact.com/pc/products/0303367>



Female test connector, color: yellow

Female test connector

Female test connector - PSBJ 4/15/6 GN - 0303370

<https://www.phoenixcontact.com/pc/products/0303370>



Female test connector, color: green

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Female test connector

Female test connector - PSBJ 4/15/6 VT - 0303383

<https://www.phoenixcontact.com/pc/products/0303383>



Female test connector, color: violet

Female test connector

Female test connector - PSBJ 4/15/6 GY - 0303396

<https://www.phoenixcontact.com/pc/products/0303396>



Female test connector, color: gray

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>



Female test connector

Female test connector - PSBJ 4/15/6 BK - 0303406

<https://www.phoenixcontact.com/pc/products/0303406>



Female test connector, color: black

Female test connector

Female test connector - PSB 4/7/6 - 0303299

<https://www.phoenixcontact.com/pc/products/0303299>



Female test connector, color: silver

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Test plugs

Test plugs - PS-MT - 0311647

<https://www.phoenixcontact.com/pc/products/0311647>



Test plugs, color: silver

Marker for terminal blocks

Marker for terminal blocks - UC-TM 8 - 0818072

<https://www.phoenixcontact.com/pc/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap in, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

Feed-through terminal block - UK 6 N



3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Marker for terminal blocks

Marker for terminal blocks - UC-TM 8 CUS - 0824597

<https://www.phoenixcontact.com/pc/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 8 - 0828740

<https://www.phoenixcontact.com/pc/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap in, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 8 CUS - 0829616

<https://www.phoenixcontact.com/pc/products/0829616>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

Marker for terminal blocks

Marker for terminal blocks - ZB 8,LGS:L1-N,PE - 1052413

<https://www.phoenixcontact.com/pc/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Warning label

Warning label - WS 5- 8 - 1004416

<https://www.phoenixcontact.com/pc/products/1004416>

Warning plate, with 2 plastic screws, across 5 terminal blocks, pitch 8 mm



Warning label

Warning label - WS 4- 8 - 1004212

<https://www.phoenixcontact.com/pc/products/1004212>

Warning plate, with 2 plastic screws, across 4 terminal blocks, pitch 8 mm



Feed-through terminal block - UK 6 N

3004524

<https://www.phoenixcontact.com/pc/products/3004524>

Warning label

Warning label - WS 3- 8 - 1004128

<https://www.phoenixcontact.com/pc/products/1004128>

Warning plate, with 2 plastic screws, across 3 terminal blocks, pitch 8 mm



Bridge

Bridge - ISSBI 10- 8 - 0301534

<https://www.phoenixcontact.com/pc/products/0301534>

Bridge, pitch: 8 mm, color: silver



 Max. current carrying capacity: 57 A

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)