

https://www.phoenixcontact.com/in/products/3030187



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, pitch: 5.2 mm, color: red

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step



https://www.phoenixcontact.com/in/products/3030187



Commercial Data

| Order Key | 3030187 |
|--------------------------------------|--------------------|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales Key | BE2 |
| Product Key | BE2Z2X |
| Catalog Page | Page 70 (C-1-2019) |
| GTIN | 4017918193829 |
| Weight per Piece (including packing) | 3.43 g |
| Weight per Piece (excluding packing) | 3.35 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |



https://www.phoenixcontact.com/in/products/3030187



Technical Data

| D | | |
|----------|------------|---|
| Product | properties | ς |
| | | |

| Number of positions | 4 | |
|---------------------|---|--|
| | | |

Electrical properties

| Maximum load current | 24 A (The current values for the jumpers can deviate when used |
|----------------------|---|
| | in different modular terminal blocks. The precise values can be |
| | found in the accessories data for the respective modular terminal |
| | blocks.) |

Connection data

| Maximum load current | 24 A (The current values for the jumpers can deviate when used |
|----------------------|---|
| | in different modular terminal blocks. The precise values can be |
| | found in the accessories data for the respective modular terminal |
| | blocks.) |

Dimensions

| Width | 19.4 mm |
|--------|---------|
| Height | 3 mm |
| Length | 22.7 mm |
| Pitch | 5.2 mm |

Material specifications

| Color | red |
|--|--------|
| Material | Copper |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |

Mounting

| Mounting type | Plug-in mounting |
|---------------|------------------|
| | |



https://www.phoenixcontact.com/in/products/3030187



Classifications

ECLASS

| ECLASS-9.0 | 27141140 |
|---------------|----------|
| ECLASS-10.0.1 | 27141140 |
| ECLASS-11.0 | 27141140 |

ETIM

UNSPSC

| UNSPSC 19.0 | 39121426 |
|-------------|----------|
| UNSPSC 20.0 | 39121426 |
| UNSPSC 21.0 | 39121426 |

3030187

https://www.phoenixcontact.com/in/products/3030187



Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |



https://www.phoenixcontact.com/in/products/3030187



Accessories

Front cutter

Front cutter - CUTFOX-FBS - 1212124



Cutting tool, for separating individual jumper bars from FBS \dots plug-in bridges and EB \dots insertion bridges

Protective cap

Protective cap - FBSC - 3012325



Covering hood, provides reliable shock protection when using cut-to-length FBS . ..-5 and FBS ...-6 bridges, color: red

Phoenix Contact 2022 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in

单击下面可查看定价,库存,交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)