

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Crimp contact, nominal current: 6 A, contact surface: Tin



Commercial data

Item number	1340361
Packing unit	200 pc
Minimum order quantity	200 pc
Note	Made to order (non-returnable)
Sales key	*****
Product key	AABCUB
GTIN	4063151646462
Weight per piece (including packing)	0.442 g
Weight per piece (excluding packing)	0.474 g
Customs tariff number	85366990
Country of origin	CN

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

Technical data

Product properties

Product type	Crimp contact
Product family	D3PC-MP-F

Connection data

Stripping length	4.5 mm
Conductor cross section AWG	24 ... 20

Material specifications

Contact surface	Tin Sn
Contact surface material	Tin
Metal surface terminal point (top layer)	Tin (1 - 3 µm Sn)
Metal surface contact area (top layer)	Tin (1 - 3 µm Sn)
Surface characteristics	hot-dip tin-plated
Contact material	Cu alloy

Electrical properties

Nominal current I_N	6 A
-----------------------	-----

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

Classifications

ECLASS

ECLASS-11.0	27460291
ECLASS-12.0	27460291
ECLASS-13.0	27460291

ETIM

ETIM 9.0	EC002637
----------	----------

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

Accessories

D3-MP RELEASE TOOL - Removal tool

1441450

<https://www.phoenixcontact.com/in/products/1441450>



Crimping tool, color: black, product range: Accessories, width: 7 mm

D32PC 2,2/ 2-5,08-X - PCB connector

1376522

<https://www.phoenixcontact.com/in/products/1376522>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 1, number of positions: 2, product range: D32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS D, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

D32PC 2,2/ 2-5,08-Y - PCB connector

1376499

<https://www.phoenixcontact.com/in/products/1376499>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 1, number of positions: 2, product range: D32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS D, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D32PC 2,2/ 3-5,08-Z - PCB connector

1378299

<https://www.phoenixcontact.com/in/products/1378299>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 1, number of positions: 3, product range: D32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS D, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

DD32PC 2,2/ 4-5,08-XX - PCB connector

1376625

<https://www.phoenixcontact.com/in/products/1376625>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 2, number of positions: 4, product range: DD32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS DD, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

DD32PC 2,2/ 6-5,08-YY - PCB connector

1378302

<https://www.phoenixcontact.com/in/products/1378302>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 2, number of positions: 6, product range: DD32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS DD, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact



1340361

<https://www.phoenixcontact.com/in/products/1340361>

DD32PC 2,2/ 6-5,08-XY - PCB connector

1378263

<https://www.phoenixcontact.com/in/products/1378263>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 320 V, contact connection type: Socket, number of rows: 2, number of positions: 6, product range: DD32PC 2,2/..., pitch: 5.08 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS DD, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D31PC 2,2/ 2-3,81-X - PCB connector

1337548

<https://www.phoenixcontact.com/in/products/1337548>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact connection type: Socket, number of rows: 1, number of positions: 2, product range: D31PC 2,2/..., pitch: 3.81 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS D, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact

1340361

<https://www.phoenixcontact.com/in/products/1340361>

D31PC 2,2/ 3-3,81-Y - PCB connector

1340903

<https://www.phoenixcontact.com/in/products/1340903>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact connection type: Socket, number of rows: 1, number of positions: 3, product range: D31PC 2,2/..., pitch: 3.81 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS D, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

DD31PC 2,2/ 4-3,81-X - PCB connector

1340465

<https://www.phoenixcontact.com/in/products/1340465>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact connection type: Socket, number of rows: 2, number of positions: 4, product range: DD31PC 2,2/..., pitch: 3.81 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS DD, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

D3PC-MP 0.20-0.50-F-SN-L - Crimp contact

1340361

<https://www.phoenixcontact.com/in/products/1340361>



DD31PC 2,2/ 4-3,81-Y - PCB connector

1341274

<https://www.phoenixcontact.com/in/products/1341274>



PCB connector, color: black, nominal current: 8 A, rated voltage (III/2): 160 V, contact connection type: Socket, number of rows: 2, number of positions: 4, product range: DD31PC 2,2/..., pitch: 3.81 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: CONNEXIS DD, locking: Snap-in locking, mounting: Self-locking flange, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)