

# Snap-in markers - UCT-EM (6X10) CUS



0801579

<https://www.phoenixcontact.com/in/products/0801579>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---

UniCard sheet, for labeling devices from other manufacturers, for overview table see download area, labeled according to customer specifications



# Snap-in markers - UCT-EM (6X10) CUS



0801579

<https://www.phoenixcontact.com/in/products/0801579>

## Commercial Data

Order Key	0801579
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BG8
Product Key	BG8148
Catalog Page	Page 248 (C-5-2013)
GTIN	4046356683166
Weight per Piece (including packing)	14.9 g
Weight per Piece (excluding packing)	10.9 g
Customs tariff number	49119900
Country of origin	PL

# Snap-in markers - UCT-EM (6X10) CUS



0801579

<https://www.phoenixcontact.com/in/products/0801579>

## Technical Data

### Product properties

#### Marking

Number of individual labels	54
Number of individual labels per row	9

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
---------------------------------	-------------------

### Mounting

Mounting type	snapped into marker carrier
---------------	-----------------------------

### Material specifications

Color	white
RoHS compliant	Yes
Material	PC
Flammability rating according to UL 94	V0
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Specification	VW PV 3.10.7:2005-02
Result	Test passed

#### Weathering-resistance

Specification	Following ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

#### Wipe resistance of inscriptions

Specification	IEC 61010-1:2010-06
Result	Test passed

#### Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
---------------------------------	-------------------

# Snap-in markers - UCT-EM (6X10) CUS



0801579

<https://www.phoenixcontact.com/in/products/0801579>

## Dimensions

Width	6 mm
Length	10 mm

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# Snap-in markers - UCT-EM (6X10) CUS



0801579

<https://www.phoenixcontact.com/in/products/0801579>

## Classifications

### ECLASS

ECLASS-9.0	27400629
ECLASS-10.0.1	27400629
ECLASS-11.0	27281103

### ETIM

ETIM 6.0	EC000761
----------	----------

### UNSPSC

UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)