

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Feed-through terminal block, nom. voltage: 500 V, nominal current: 17.5 A, connection method: Screw connection, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Your advantages

- Universal foot which can be used on NS 35... and NS 32... DIN rails
- The UK universal screw terminal block series has the typical features which are decisive for practical applications
- Potential distribution via fixed bridges in the terminal center or insertion bridges in the clamping space

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3005837 |
| Packing unit | 50 pc |
| Minimum order quantity | 1 pc |
| Product Key | BE1211 |
| Catalog Page | Page 458 (C-1-2019) |
| GTIN | 4017918139179 |
| Weight per Piece (including packing) | 5.296 g |
| Weight per Piece (excluding packing) | 4.29 g |
| Customs tariff number | 85369010 |
| Country of origin | CN |

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Technical Data

Product properties

| | |
|-----------------------|-----------------------------|
| Product type | Feed-through terminal block |
| Number of connections | 2 |
| Number of rows | 1 |
| Potentials | 1 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|---|--------|
| Rated surge voltage | 6 kV |
| Maximum power dissipation for nominal condition | 0.56 W |

Connection data

| | |
|---------------------------------|---------------------|
| Number of connections per level | 2 |
| Nominal cross section | 1.5 mm ² |

Level 1 above 1 below 1

| | |
|---|---|
| Screw thread | M2 |
| Tightening torque | 0.22 ... 0.25 Nm |
| Stripping length | 7 mm |
| Internal cylindrical gage | A1 |
| Conductor cross section solid | 0.14 mm ² ... 1.5 mm ² |
| Cross section AWG | 26 ... 16 |
| Conductor cross section flexible | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section, flexible [AWG] | 26 ... 16 |
| Flexible conductor cross section flexible (ferrule, w/o plastic sleeve) | 0.25 mm ² ... 0.75 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.25 mm ² ... 0.75 mm ² |
| 2 conductors with same cross section, solid | 0.14 mm ² ... 0.75 mm ² |
| 2 conductors with same cross section, flexible | 0.14 mm ² ... 0.75 mm ² |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve | 0.25 mm ² ... 0.34 mm ² |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm ² ... 0.5 mm ² |
| Nominal current | 17.5 A |
| Maximum load current | 17.5 A (with 1.5 mm ² conductor cross section) |
| Nominal voltage | 500 V |
| Nominal cross section | 1.5 mm ² |

Ex data

Rated data (ATEX/IECEx)

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

| | |
|--|---|
| ATEX certificate | KEMA 98 ATEX 1651 U |
| IEC Ex certificate | IECEX KEM 06.0034 U |
| Identification | Ex eb IIC Gb |
| Operating temperature range | -60 °C ... 110 °C |
| Ex-certified accessories | 3001022 D-UK 2,5 1205037 SZS 0,4X2,5 VDE 1201442 E/UK |
| Bridge data | 15.5 A / 1.5 mm ² |
| Ex temperature increase | 40 K (17.5 A / 1.5 mm ²) |
| Rated voltage | 320 V |
| for bridging with bridge | 352 V |
| - At bridging between non-adjacent terminal blocks | 69 V |
| Rated insulation voltage | 320 V |

Ex level General

| | |
|----------------------|---------|
| Rated current | 15.5 A |
| Maximum load current | 15.5 A |
| Contact resistance | 0.45 mΩ |

Ex connection data General

| | |
|---|---|
| Torque range | 0.22 Nm ... 0.25 Nm |
| Nominal cross section | 1.5 mm ² |
| Rated cross section AWG | 16 |
| Connection capacity rigid | 0.14 mm ² ... 1.5 mm ² |
| Connection capacity AWG | 26 ... 16 |
| Connection capacity flexible | 0.14 mm ² ... 1.5 mm ² |
| Connection capacity AWG | 26 ... 16 |
| 2 conductors with same cross section, solid | 0.14 mm ² ... 0.75 mm ² |
| 2 conductors with the same cross-section AWG rigid | 26 ... 18 |
| 2 conductors with same cross section, stranded | 0.14 mm ² ... 0.75 mm ² |
| 2 conductors with the same cross-section AWG flexible | 26 ... 18 |

Dimensions

| | |
|------------------|---------|
| Width | 4.2 mm |
| End cover width | 1.5 mm |
| Height NS 35/15 | 49.5 mm |
| Height NS 35/7,5 | 42 mm |
| Height | 1.654 " |
| Height NS 32 | 47 mm |
| Length | 42.5 mm |

Material specifications

| | |
|--|------|
| Color | gray |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

| | |
|---|-------------|
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 28 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Electrical tests

Surge voltage test

| | |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV |
| Result | Test passed |

Temperature-rise test

| | |
|--|-------------------------------------|
| Requirement temperature-rise test | Increase in temperature \leq 45 K |
| Result | Test passed |
| Short-time withstand current 1.5 mm ² | 0.18 kA |
| Result | Test passed |

Power-frequency withstand voltage

| | |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV |
| Result | Test passed |

Mechanical properties

Mechanical data

| | |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

Mechanical tests

Mechanical strength

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

Attachment on the carrier

| | |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint | 1 N |
| Result | Test passed |

Test for conductor damage and slackening

| | |
|----------------|--------|
| Rotation speed | 10 rpm |
| Revolutions | 135 |

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

| | |
|--------------------------------|-------------------------------|
| Conductor cross section/weight | 0.14 mm ² / 0.2 kg |
| | 1.5 mm ² / 0.4 kg |
| Result | Test passed |

Environmental and real-life conditions

Needle-flame test

| | |
|------------------|-------------|
| Time of exposure | 30 s |
| Result | Test passed |

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Standards and regulations

| | |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

Mounting

| | |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
| | NS 35/15 |
| | NS 32 |

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>



Drawings

Circuit diagram



Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Approvals

| DNV Approval ID: TAE00001CT | | | | |
|---------------------------------------|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | | | - | - |

| EAC Approval ID: RU C-DE.A*30.B.01742 | | | | |
|---|--|--|--|--|
|---|--|--|--|--|

| cULus Recognized Approval ID: E60425 | | | | |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| Use group B | 300 V | 15 A | 30 - 14 | - |
| Use group C | 300 V | 15 A | 30 - 14 | - |
| Use group F | 500 V | 15 A | 30 - 14 | - |
| Use group D | 600 V | 5 A | 30 - 14 | - |

| KR Approval ID: HMB17372-EL001 | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

| BV Approval ID: 07774/E0 BV | | | | |
|---------------------------------------|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | | | - | - |

| ATEX Approval ID: KEMA98ATEX1651U | | | | |
|---|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| Type examination certificate | 352 V | 17 A | - | 0.14 - 1.5 |

| EAC Ex Approval ID: RU C-DE.HA91.B.00066 | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>



IECEX

Approval ID: IECEX KEM 06.0034U

| Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
|-----------------------|-----------------------|-------------------|-----------------------------|
| 352 V | 17 A | - | 0.14 - 1.5 |



CCC

Approval ID: 2020322313000623



NEPSI

Approval ID: GYJ20.1195U

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27141120 |
| ECLASS-10.0.1 | 27141120 |
| ECLASS-11.0 | 27141120 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000897 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Accessories

Partition plate

Partition plate - ATP-UK - 3003224

<https://www.phoenixcontact.com/pc/products/3003224>



Partition plate, length: 56 mm, width: 1.5 mm, height: 45.7 mm, color: gray

Screwdriver

Screwdriver - SZS 0,4X2,5 VDE - 1205037

<https://www.phoenixcontact.com/pc/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

End clamp

End clamp - CLIPFIX 35 - 3022218

<https://www.phoenixcontact.com/pc/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

End clamp

End clamp - CLIPFIX 35-5 - 3022276

<https://www.phoenixcontact.com/pc/products/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

End clamp

End clamp - E/NS 35 N - 0800886

<https://www.phoenixcontact.com/pc/products/0800886>

End clamp, width: 9.5 mm, color: gray



End clamp

End clamp - E/UK - 1201442

<https://www.phoenixcontact.com/pc/products/1201442>

End clamp, material: PA, color: gray, Mounting on a DIN rail NS 32 or NS 35



Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

End clamp

End clamp - E/UK 1 - 1201413

<https://www.phoenixcontact.com/pc/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

Test adapter

Test adapter - PAI-4 - 3030925

<https://www.phoenixcontact.com/pc/products/3030925>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, color: gray

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

End cover

End cover - D-UK 2,5 - 3001022

<https://www.phoenixcontact.com/pc/products/3001022>

End cover, length: 42.5 mm, width: 1.5 mm, height: 30.7 mm, color: gray



End cap

End cap - NS 35/ 7,5 CAP - 1206560

<https://www.phoenixcontact.com/pc/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>



End cap

End cap - NS 35/15 CAP - 1206573

<https://www.phoenixcontact.com/pc/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



DIN rail, unperforated

DIN rail, unperforated - NS 32 UNPERF 2000MM-VPE 10 - 1201015

<https://www.phoenixcontact.com/pc/products/1201015>

DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)



Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

<https://www.phoenixcontact.com/pc/products/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - 1204122

<https://www.phoenixcontact.com/pc/products/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

<https://www.phoenixcontact.com/pc/products/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

<https://www.phoenixcontact.com/pc/products/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>



DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - 0801762

<https://www.phoenixcontact.com/pc/products/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714

<https://www.phoenixcontact.com/pc/products/1201714>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 WH UNPERF 2000MM-VPE 10 - 1204135

<https://www.phoenixcontact.com/pc/products/1204135>



DIN rail, unperforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756

<https://www.phoenixcontact.com/pc/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586

<https://www.phoenixcontact.com/pc/products/1206586>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM-VPE 10 - 1201895

<https://www.phoenixcontact.com/pc/products/1201895>



DIN rail, unperforated, similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>



DIN rail, unperforated

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM-VPE 10 - 1201798

<https://www.phoenixcontact.com/pc/products/1201798>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver, Pack of 10 (20 m)

Fixed bridge

Fixed bridge - FBRN 8-4 N - 3001608

<https://www.phoenixcontact.com/pc/products/3001608>



Fixed bridge, pitch: 4 mm, color: silver

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Fixed bridge

Fixed bridge - FBRN 7-4 N - 3001598

<https://www.phoenixcontact.com/pc/products/3001598>



Fixed bridge, color: silver

Fixed bridge

Fixed bridge - FBRN 6-4 N - 3001585

<https://www.phoenixcontact.com/pc/products/3001585>



Fixed bridge, color: silver

Feed-through terminal block - UK 1,5 N


3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Fixed bridge

Fixed bridge - FBRN 5-4 N - 3001572

<https://www.phoenixcontact.com/pc/products/3001572>




Fixed bridge, color: silver

Fixed bridge

Fixed bridge - FBRN 4-4 N - 3001569

<https://www.phoenixcontact.com/pc/products/3001569>



Fixed bridge, pitch: 4 mm, color: silver

Feed-through terminal block - UK 1,5 N

3005837


<https://www.phoenixcontact.com/pc/products/3005837>



Fixed bridge

Fixed bridge - FBRN 20-4 N - 3001637

<https://www.phoenixcontact.com/pc/products/3001637>



Fixed bridge, color: silver

Fixed bridge

Fixed bridge - FBRN 10-4 N - 3001624

<https://www.phoenixcontact.com/pc/products/3001624>



Fixed bridge, pitch: 4.2 mm, color: silver

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Zack marker strip

Zack marker strip - ZB 4 :UNBEDRUCKT - 0805001

<https://www.phoenixcontact.com/pc/products/0805001>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snap in, for terminal block width: 4.2 mm, lettering field size: 4.2 x 10.5 mm, Number of individual labels: 10

Zack marker strip

Zack marker strip - ZB 4 CUS - 0824951

<https://www.phoenixcontact.com/pc/products/0824951>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 4.2 mm, lettering field size: 4.2 x 10.5 mm, Number of individual labels: 10

Feed-through terminal block - UK 1,5 N


3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Zack marker strip

Zack marker strip - ZB 4,LGS:FORTL.ZAHLEN - 0805739

<https://www.phoenixcontact.com/pc/products/0805739>




Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, for terminal block width: 4.2 mm, lettering field size: 4.2 x 10.5 mm, Number of individual labels: 10

Zack marker strip

Zack marker strip - ZB 4,QR:FORTL.ZAHLEN - 0805807

<https://www.phoenixcontact.com/pc/products/0805807>



Zack marker strip, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snap into tall marker groove, for terminal block width: 4.2 mm, lettering field size: 4.2 x 10.5 mm, Number of individual labels: 10

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail perforated

DIN rail perforated - NS 32 PERF 2000MM-VPE 10 - 1201002

<https://www.phoenixcontact.com/pc/products/1201002>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

<https://www.phoenixcontact.com/pc/products/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

<https://www.phoenixcontact.com/pc/products/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

<https://www.phoenixcontact.com/pc/products/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail perforated

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

<https://www.phoenixcontact.com/pc/products/1201730>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail perforated

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602

<https://www.phoenixcontact.com/pc/products/0806602>



DIN rail perforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white, Pack of 25 (50 m)

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

DIN rail perforated

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599

<https://www.phoenixcontact.com/pc/products/1206599>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Marker for terminal blocks

Marker for terminal blocks - UC-TM 4 - 0818111

<https://www.phoenixcontact.com/pc/products/0818111>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap in, for terminal block width: 4.2 mm, lettering field size: 3.6 x 10.5 mm, Number of individual labels: 120

Feed-through terminal block - UK 1,5 N

3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Marker for terminal blocks

Marker for terminal blocks - UC-TM 4 CUS - 0824573

<https://www.phoenixcontact.com/pc/products/0824573>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 4.2 mm, lettering field size: 3.6 x 10.5 mm, Number of individual labels: 120

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 4 - 0828732

<https://www.phoenixcontact.com/pc/products/0828732>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap in, for terminal block width: 4.2 mm, lettering field size: 3.6 x 10.5 mm, Number of individual labels: 84

Feed-through terminal block - UK 1,5 N



3005837

<https://www.phoenixcontact.com/pc/products/3005837>

Marker for terminal blocks

Marker for terminal blocks - UCT-TM 4 CUS - 0829588

<https://www.phoenixcontact.com/pc/products/0829588>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 4.2 mm, lettering field size: 3.6 x 10.5 mm, Number of individual labels: 84

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)