



Series: Internal Antenna

PART NUMBER: W3334XXXXX



Features:

- Peak gain 4/5.5dBi
- VSWR 2:1
- Mounting with adhesive tape
- Ultra small flexible radiator 4.3x15.3x0.1mm
- See connector and cable options page 2

Applications:

- 2.4/5.xGHz radios
- Dualband WiFi
- Bluetooth, BLE, ZigBee
- DSRC 5.85-5.925GHz
- Routers, set top boxes
- IoT, M2M, V2x

All dimensions are in mm / inches

Issue: 1922

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100

Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA

Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 1-360-944-755 Downloaded From Oneyac.com

Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



TECHNICAL DATA SHEET

Description: FPC Antenna 2.4/5.xGHz/DSRC

Series: Internal Antenna

PART NUMBER: W3334XXXX

This document covers all product variants of the following product family:

W3334B0100	100mm 1.13mm OD cable	U.FL compatible connector
W3334B0127	127mm 1.13mm OD cable	U.FL compatible connector
W3334B0150	150mm 1.13mm OD cable	U.FL compatible connector
W3334B0250	250mm 1.13mm OD cable	U.FL compatible connector
W3334B0290	290mm 1.13mm OD cable	U.FL compatible connector
W3334BD0150	150mm 0.81mm OD cable	MHF4 compatible connector

Issue: 1922

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

For more information:



Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany

Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998





Series: Internal Antenna

PART NUMBER: W3334XXXXX

ELECTRICAL SPECIFICATIONS

Cable Length (mm)	P/N	Frequency (MHz)	Peak Gain (dBi)	Efficiency (%)	VSWR
100	W3334B0100	2400-2500	4+/-1dB	50	2:1
		4900-6000	5.5+/-1dB	70	2.5:1
127	W3334B0127	2400-2500	4+/-1dB	50	2:1
		4900-6000	5.5+/-1dB	70	2:1
150	W3334B0150 W3334BD0150	2400-2500	4+/-1dB	50	2:1
		4900-6000	5.5+/-1dB	70	2:1
250	W3334B0250	2400-2500	4+/-1dB	50	2:1
		4900-6000	5.5+/-1dB	70	2:1
290	W3334B0290	2400-2500	4+/-1dB	50	2:1
		4900-6000	5.5+/-1dB	70	2:1

Typical free space performance measured on 1mm thick PC plate





TECHNICAL DATA SHEET

Description: FPC Antenna 2.4/5.xGHz/DSRC

Series: Internal Antenna

PART NUMBER: W3334XXXXX

MECHANICAL SPECIFICATIONS

FPC size 14.3 X 5.3 X0.1[0.56 X 0.21 X 0.004] mm[inch]

Connector type

See Page 2.

Cable type

See Page 2

Cable length

Optional

Cable color

Black

Adhesive

3M467

ENVIRONMENTAL SPECIFICATIONS

Operating temperature

-40/+85 ° C







Series: Internal Antenna

PART NUMBER: W3334XXXXX

MECHANICAL DRAWING










Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS

VSWR

W3334 measured with polycarbonate plate



-W3334 ----Spec

Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable



TECHNICAL DATA SHEET


Description: FPC Antenna 2.4/5.xGHz/DSRC

Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS

Efficiency



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable








Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS

Peak Gain



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable

Issue: 1922

ROHS






Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable






Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable








Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable








Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable








Series: Internal Antenna

PART NUMBER: W3334XXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable

Issue: 1922

ROHS






Series: Internal Antenna

PART NUMBER: W3334XXXXX

CHARTS



Note: Antenna tested on 1mm thickness PC plate with 150mm feed cable







Series: Internal Antenna

PART NUMBER: W3334XXXXX

PACKAGING

10PCS/PE bag 10 PE bag/foam bag 12 foam bag/ carton box

Total 1200PCS/Carton box





单击下面可查看定价,库存,交付和生命周期等信息

>>Pulse(普思)