



PC Board Layout Component Side Shown
PC Board Thickness=1.6mm

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 50 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
- 5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING MATERIAL : GLASS FILLED NYLON UL94V-0 COLOR-BLACK.
- 2. INSERT MATERIAL : GLASS FILLED NYLON UL94V-0 COLOR-BLACK.
- 3. CONTACT MATERIAL : PHOSPHOR BRONZE ϕ 0.46mm.
- 4. PLATING : GOLD PLATING OVER NICKEL.
- 5. OPERATING LIFE : 750 CYCLES MIN.
- 6. PCB RETENTION PRE-SOLDER : 1 LB MIN.
- 7. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

- 1. STORAGE TEMPERATURE : -40°C TO +85°C.
- 2. OPERATION TEMPERATURE: -40°C TO +85°C.
- 3. WAVE SOLDERING TEMPERATURE: 255~265°C(5~10 SECONDS)
- 4. RoHS COMPLIANT.

MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68, SUBPART F.
CUL FILE NO. E163191

PART NUMBER
E5908-57C132-L

DETACHED LISTS MM (INCH) TOLERANCES EXCEPT AS NOTED MM .0 ± 0.2 ± .00 ± 0.15 ± .000 ± 0.075 ± ANGLES ± 0.5 THIRD ANGLE PROJECTION	RoHS Compliant			
	TITLE RJ45 STACKED GANGED JACK, 2*4			
DFTO Cathy DATE 2006/10/11		DRAWING NO. CE593A50-LA /PART NO. SEE TABLE		SIZE A3
SCALE : 1.5:1		DO NOT SCALE DRAWING		REV 0
		SHEET 1 OF 1		

单击下面可查看定价，库存，交付和生命周期等信息

[>>Pulse\(普思\)](#)