IP67 Active 6 Band GPS Antenna

Pulse Part Number W4120 Family





The W4120 family offers a multi-band, active GPS antenna combining compact size with the ability to support most international wireless services. The active GPS antenna provides exact location-based information which can be communicated using the 3G frequencies. The low profile housing is compatible with IP67 allowing for outdoor use.

Features

- Active GPS & 3G functionality
- IP 67 rated Product
- Adhesive Mounting
- Other cable and connector variations available
- RoHS Compliant Product

Applications

- Navigation and location
- Fleet management
- Intelligent vehicle safety
- Asset tracking
- Pay-as-you-drive insurance

P/N	Cable Length	Connector
W4120GG3000	9.8' (3 m)	3G - SMA Male GPS - SMA Male
W4120EG5000	16.4' (5 m)	3G - SMA Male GPS - MMCX
W4120ER5000	16.4' (5 m)	3G - MCX GPS - MMCX
W4120GG5000	16.4' (5 m)	3G - SMA Male GPS - SMA Male
W4120GL5000	16.4' (5 m)	3G - FME GPS - SMA Male

San Diego, CA 858 674 8100

Vancouver, WA 360 944 7551

Europe 49 7032 7806 0

Asia 86 755 33966678

North Asia 886 3 4356768

China 86 512 6807 9998

pulseelectronics.com/products/antennas

L113.A (03/11)

IP67 Active 6 Band GPS Antenna

Pulse Part Number W4120 Family

Electrical Specifications

Frequency 1 [MHz]		806-960
Frequency 2 [MHz]		1710-2170
Frequency 3 [MHz]		1574.4-1576.4
Nominal Impedance [Ω]		50
~	Freq 1	2.5:1
VSWR	Freq 2	2.5:1
>	Freq 3	2.0:1
Gain	Freq 1 [dBi avg]	0
Ğ	Freq 2 [dBi avg]	0
ģ	Freq 1	Linear Vertical
Polariza- tion	Freq 2	Linear Vertical
Pc	Freq 3	RHCP
Cable	Type [Freq 1/2]	RG-174
Cal	Type [GPS]	RG-174

LNA Specifications

Gain at 3V [dBic / dB ± 2)]	5 / 26
Gain at 5V [dBic / dB ± 2]	5 / 25
Noise Figure	1.5 dB max
Current Draw [mA Max]	25
Voltage [V DC]	3 - 5

Environmental Specifications

Operating Temperature [°C]	-40 to +85
Storage Temperature [°C]	-40 to +85
Relative Humidity [%]	100

Mechanical Specifications

Radome Material	PC/PET, UV resistant
Color	Black
Ingress Protection	IP67
Weight [oz/g]	4.7 / 145
Dimensions [Inches/mm]	5.4 x 1.5 x .6 [136 x 37.7 x 13.8]
Mounting	Adhesive Tape




IP67 Active 6 Band GPS Antenna


Pulse Part Number W4120 Family

Radiation Patterns


Horizontal Plane - 806-960 MHz




Horizontal Plane - 1710-2170 MHz



Vertical Plane - 806-960 MHz



Vertical Plane - 1710-2170 MHz



For More Information

Tel: 858 674 8100

Fax: 858 674 8262

 Pulse Worldwide Headquarters
 Larsen Brand Antenna:

 12220 World Trade Drive
 3611 NE 112th Avenue

 San Diego, CA 92128
 Vancouver, WA 98682

 U.S.A.
 USA

Tel: 360 944 7551 Fax: 369 944 7556 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg Germany

Tel: 49 7032 7806 0

Fax: 49 7032 7806 135

Asia Headquarters B402, Shenzhen Academy of Aerospace Technology Bldg. 10th Kejinan Road, High-Tech Zone Nanshan District, Shenzen, PR China 518057

Tel: 86 755 33966678 Fax: 86 755 33966700 Pulse North Asia 3F, No. 198, Zhongyuan Road Zhongli City, Tayyuan County

Zhongli City, Taoyuan County 320 Taiwan R. O. C.

Tel: 886 3 4356768 Fax: 886 3 4356823 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road, (#29 Bldg, 4th Phase) Suzhou New District Science & Tech Industrial Park Jiangsu Province, Suzhou 215009 PR China

Tel: 86 512 6807 9998 Fax: 86 512 6809 8023

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2010. Pulse Electronics, Inc. All rights reserved.

pulseelectronics.com/products/antennas

L113.A (03/11)



单击下面可查看定价,库存,交付和生命周期等信息

>>Pulse(普思)