



PC BOARD LAYOUT COMPONENT SIDE SHOWN

- ENVIRONMENTAL:**
1. STORAGE : -40°C TO +85°C.
 2. OPERATION: -40°C TO +85°C.
 3. WAVE SOLDERING TEMPERATURE: 230°~250°(3~5 SECONDS)
 4. ROHS COMPLIANT.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
CUL FILE NO. E163191

- MECHANICAL:**
1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
 2. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.35mm.
 3. PLATING : GOLD PLATING OVER NICKEL.
 4. OPERATING LIFE : 750 CYCLES MIN.
 5. PCB RETENTION PRE-SOLDER : 1 LB MIN.
 6. PCB RETENTION POST-SOLDER: 10 LBS MIN.

NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 35 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN. @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

PART NUMBER	GOLD PLATING	CONTACTS
E5386-E00212-L	6u"	6
E5388-E00212-L	6u"	8
E5388-E00213-L	15u"	8
E5388-E00214-L	30u"	8

DETACHED LISTS

(INCH)	(MM)
0 ± 0.2	±
.00 ± 0.15	±
.000 ± 0.075	±

ANGLES ± 0.5



RoHS Compliant

DRW: Jerr Chi DATE: 06/28/06

THIRD ANGLE PROJECTION

SCALE : 3 : 1

FULL RISE ELECTRONIC CO., LTD
TITLE 11.5 SIDE ENTRY 8P
FCC DEEP TYPE
 DRAWING NO. CE533096-01
 /PART NO. SEE NOTES
 DO NOT SCALE DRAWING

SIZE REV
 A3 0
 SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>Pulse\(普思\)](#)