



PC Board Layout Component Side Shown

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD
△		DRAWING MODIFY	3/19/99	LWS
△		DRAWING MODIFY	4/4/99	LWS
△		NOTE MODIFY	4/4/99	SYZ
△		DRAWING MODIFY	07/14/00	SHY
△		DRAWING&P/N MODIFY	03/18/02	p8p
△		DRAWING MODIFY	12/28/2003	Syngs
△		ADD PART NO	1/02/2004	LUXIN
△		ADD PART NO	01/28/05	LUXIN
△		NOTE MODIFY	01/28/05	LUXIN
△		DEL ROHS P/N	01/23/05	Qianpu

NOTES:

ELECTRICAL:

- VOLTAGE RATING : 125 VAC RMS.
- CURRENT RATING : 1.5 AMP.
- CONTACT RESISTANCE : 45 MILLIOHMS MAX.
- INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
- DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

- HOUSING MATERIAL : PBT OR FR52.
- CONTACT MATERIAL : PHOSPHOR BRONZE ϕ 0.46mm.
- PLATING : GOLD PLATING OVER NICKEL.
- OPERATING LIFE : 750 CYCLES MIN.
- PCB RETENTION PRE-SOLDER : 1 LB MIN.
- PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

- STORAGE : -40°C TO +85°C.
 - OPERATION: 0°C TO 70°C.
- MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68, SUBPART F.
CUL FILE NO. E163191

PART NUMBER: E556X-20AXXX

NO. OF CONTACT		1- 3u" 2- 6u" 3-15u"
2-2 CONTACTS		4-30u" 5-50u" 6-Pd20u"
4-4 CONTACTS	5-BK	△7-Pd30u" 8-Pd10u"
6-6 CONTACTS	D-GY	
	U-FR52 BK △	1-W/ PANEL STOP
		2-W/O PANEL STOP

DETACHED LISTS	MM (INCH)	DFTO SYZ	DATE 3/2/99	FULL RISE ELECTRONIC CO., LTD
	TOLERANCES EXCEPT AS NOTED	CHKDYICAN	DATE 2005/4/23	
		MFO	DATE	
		APPVLSAMMY	DATE 2005/4/23	
	MM			TITLE
	.0 ±0.20	±		MINI L/P SIDE ENTRY PCB JACK 6P
	.00 ±0.15	±		DRAWING NO. GE553009
	.000 ±0.075	±		/PART NO. SEE NOTE
	ANGLES ±			SIZE A3
	THIRD ANGLE PROJECTION	FINISH:	SCALE : 3:1	REV 10
			DO NOT SCALE DRAWING	SHEET X OF Y

单击下面可查看定价，库存，交付和生命周期等信息

[>>Pulse\(普思\)](#)