

Dimensions in inches and (millimeters)

## FEATURES

- ◆ Ideal for printed circuit board
- ◆ Reliable low cost construction utilizing molded plastic technique
- ◆ High temperature soldering guaranteed: 260°C/10 seconds at 5 lbs., (2.3kg) tension
- ◆ Small size, simple installation
- ◆ High surge current capability

## MECHANICAL DATA

**Case:** Molded plastic body  
**Terminals:** Plated leads solderable per MIL-STD-750, Method 2026  
**Polarity:** Polarity symbols marked on case  
**Mounting Position:** Any  
**Weight:** 0.008 ounce, 0.22 grams






## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load derate current by 20%.

TWGMC Catalog Number	SYMBOLS	MB1S	MB2S	MB4S	MB6S	MB8S	MB10S	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	100	200	400	600	800	1000	VOLTS
Maximum RMS voltage	$V_{RMS}$	70	140	280	420	560	700	VOLTS
Maximum DC blocking voltage	$V_{DC}$	100	200	400	600	800	1000	VOLTS
Maximum average forward rectified current at $T_c=30^\circ\text{C}$ On glass-epoxy P.C.B. On aluminum substrate	$I_{F(AV)}$	1.0						Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	35						Amps
Maximum instantaneous forward voltage drop per leg at 0.4A	$V_F$	1.1						Volts
Maximum DC reverse current at rated DC blocking voltage $T_A=25^\circ\text{C}$ $T_A=125^\circ\text{C}$	$I_R$	5.0 500						$\mu\text{A}$ $\mu\text{A}$
Typical junction capacitance per leg (Note3)	$C_J$	13						pF
Typical thermal resistance per leg	$R(\theta)_{JA}$	70						$^\circ\text{C/W}$
Operating temperature range	$T_J$	-55 to +150						$^\circ\text{C}$
storage temperature range	$T_{STG}$	-55 to +150						$^\circ\text{C}$

NOTES: 1. On glass epoxy P.C.B. mounted on 0.05x0.05"(1.3x1.3mm) pads  
 2. On aluminum substrate P.C.B. with on area of 0.8"x0.8"(20x20mm) mounted on 0.05X0.05"(1.3X1.3mm) solder pad  
 3. Measured at 1.0MHz and applied reverse voltage of 4.0 volts.

# RATINGS AND CHARACTERISTIC CURVES MB1S THRU MB10S



The cruve graph is for reference only, can't be the basis for judgment(曲线图仅供参考)

单击下面可查看定价，库存，交付和生命周期等信息

[>>RCD\(达标电子\)](#)