

SAW Components

Data Sheet R2712





SAW Components R2712
Resonator 804.50 MHz

Data Sheet


Features

- 2-port resonator
- nominal 180°-phase at resonance
- Provides reliable, fundamental mode, quartz frequency stabilization i.e. in transmitters or local oscillators
- Passivation layer: Protec

Terminals

■ Ni, gold plated

SMD Ceramic package QCC8C




Dimensions in mm, approx. weight 0,1 g

Pin configuration

2	Input / Ouptput
6	Output / Input

7 Ground (Input / Output) 3 Ground (Output / Input)

4,8 Ground (case)



Туре	Ordering code	Marking and Package	Packing
		according to	according to
R2712	B39801-R2712-U310	C61157-A7-A56	F61074-V8169-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T_{A}	-45/+85	°C	
Storage temperature range	$T_{\rm stg}$	-45/+85	°C	
DC voltage	$V_{\rm DC}$	0	V	between any terminals
Source power	P_{s}	0	dBm	



SAW Components R2712

Resonator 804.50 MHz

Data Sheet

Characteristics

Reference temperature: $T_{\rm A}=25\,^{\circ}{\rm C}$ Terminating Source impedance: $Z_{\rm S}=50\,\Omega$ Terminating Load impedance: $Z_{\rm L}=50\,\Omega$

		min.	typ.	max.	
Center frequency	f _c	804,25	804.5	804,75	MHz
(center frequency between 3 dB points)					
Minimum insertion attenuation	α_{min}	_	6,3	8,3	dB
Phase at f _c	φ		140		° el.
Loaded quality factor	Q_L	3000	3700		
Unloaded quality factor	Q_U	6300	7500	_	
Ageing of f _c		_	_	-10/+40	ppm
Equivalent circuit elements					
Motional capacitance	C_1	_	0,293	_	fF
Motional inductance	L_1	_	133,8	_	μН
Motional resistance	R_1	_	91	_	Ω
Input / Output capacitance	C_0	_	1,6	_	pF
Temperature coefficient of frequency 1)	TC _f	_	-0,03	_	ppm/K ²
Turnover temperature	T_0	15	_	35	°C

¹⁾ Temperature dependence of f_c : $f_c(T_A) = f_c(T_0)(1 + TC_f(T_A - T_0)^2)$



SAW Components R2712

Resonator 804.50 MHz

Data Sheet

Published by EPCOS AG Surface Acoustic Wave Components Division, SAW CE AE PD P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2003. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

4 Oct 02, 2003

单击下面可查看定价,库存,交付和生命周期等信息

>>Qualcomm-RF360