

# Multilayer Power Inductor

## CIG21L Series (2012/ EIA 0805)




### APPLICATION

Mobile phones, DSC, DVC, PDA etc. for DC-DC Converter


### FEATURES

- Low DC resistance
- Magnetically shielded structure
- Free of all RoHS-regulated substances
- Monolithic structure for high reliability

### RECOMMENDED LAND PATTERN



### DIMENSION



TYPE	Dimension [mm]			
	L	W	T	D
21	2.0±0.1	1.25±0.1	0.9±0.1	0.5+0.2 -0.3

### DESCRIPTION

Part no.	Size (inch/mm)	Inductance (uH)@1MHz	DC Resistance(Ω)	Rated Current (A) Max.
CIG21LR47MNE	0805/2012	0.47 ±20 %	0.080 ±20 %	1.30
CIG21L1R0MNE	0805/2012	1.0 ±20 %	0.110 ±20 %	1.15
CIG21L1R2MNE	0805/2012	1.2 ±20 %	0.125 ±20 %	1.10
CIG21L1R5MNE	0805/2012	1.5 ±20 %	0.140 ±20 %	1.05
CIG21L2R2MNE	0805/2012	2.2 ±20 %	0.160 ±20 %	0.95
CIG21L3R3MNE	0805/2012	3.3 ±20 %	0.220 ±20 %	0.80
CIG21L4R7MNE	0805/2012	4.7 ±20 %	0.260 ±20 %	0.75


※Rated Current: DC current value when the self-generation of heat rises to 40℃ (Reference ambient temperature:25℃)

※Operating temperature range: -40 to +125℃ (Including self-temperature rise)


※Test equipment: Agilent :E4991A+16092A

### CHARACTERISTIC DATA

1) Frequency characteristics (Typ.)



2) DC Bias characteristics (Typ.)




**PRODUCT IDENTIFICATION**

**CI G 21 L 1R0 M N E**  
**(1) (2) (3) (4) (5) (6) (7) (8)**


- (1) Chip Inductor
- (2) Power Inductor
- (3) Dimension
- (4) Product Series (L:Low RDC Type)
- (5) Inductance (R47:0.47uH, 1R0:1.0uH)
- (6) Tolerance (M:±20%)
- (7) Thickness option(N:Standard, A:Thinner than standard, B:Thicker than standard)
- (8) Packaging(C:paper tape, E:embossed tape)

**RECOMMENDED SOLDERING CONDITION**

**REFLOW SOLDERING**



**FLOW SOLDERING**



**PACKAGING**

Packaging Style	Quantity(pcs/reel)
Embossed Taping	3,000

Any data in this sheet are subject to change, modify or discontinue without notice. The data sheets include the typical data for design reference only. If there is any question regarding the data sheets, please contact our sales personnel or application engineers.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Samsung Electro-Mechanics\(三星电机\)](#)