

---

## High Sensitivity Omnipolar Hall-effect Sensor

---

### FEATURES

- Digital Omni-polar Hall-Effect sensor
- High chopping frequency
- Very high sensitivity
- Superior temperature stability
- Supports a wide voltage range
  - 2.5 to 24V
  - Operating from unregulated supply
- Reverse battery protection (up to 28V)
- Over-voltage protection at all pins
- Robust EMC performance
- Solid-state reliability
- Small package
  - 3-pin SIP -(UA)
  - 3-pin SOT23 -(SO)

### APPLICATIONS

- Flow meters
- Magnetic encoding
- Proximity sensing
- Garage door openers
- Power sliding doors
- Sunroofs motor

### DESCRIPTION

The SC246X family, produced with BiCMOS technology, is a chopper-stabilized Hall Effect Sensor that offers a magnetic sensing solution with superior sensitivity stability over temperature and integrated protection features.

Superior high-temperature performance is made possible through dynamic offset cancellation, which reduces the residual offset voltage normally caused by device over molding, temperature dependencies, and thermal stress. Each device includes on a single silicon chip a voltage regulator, Hall-voltage generator, small-signal amplifier, chopper stabilization, Schmitt trigger, and an open-drain output to sink up to 20mA.

An onboard regulator permits with supply voltages of 2.5 to 24V which makes the device suitable for a wide range of industrial and automotive applications


The SC246X is available in a 3-pin SIP and a plastic SOT23-3 surface mount package. Both packages are lead (Pb) free, with 100% matte tin lead frame plating



## CONTENTS

<b>FEATURES</b> .....	- 1 -	<i>Magnetic Characteristics</i> .....	- 7 -
<b>APPLICATIONS</b> .....	- 1 -	<b>TYPICAL CHARACTERISTIC</b> .....	- 8 -
<b>DESCRIPTION</b> .....	- 1 -	<b>TYPICAL CHARACTERISTIC (Continued)</b> .....	- 9 -
<b>BLOCK DIAGRAM</b> .....	- 3 -	<b>FUNCTIONAL DESCRIPTION</b> .....	- 10 -
<b>ORDERING INFORMATION</b> .....	- 3 -	<i>Field Direction Definition</i> .....	- 10 -
<b>TERMINAL CONFIGURATION</b> .....	- 4 -	<i>Transfer function</i> .....	- 11 -
<b>ABSOLUTE MAXIMUM RATINGS</b> .....	- 5 -	<b>TYPICAL APPLICATION</b> .....	- 12 -
<b>ESD PROTECTION</b> .....	- 5 -	<b>PACKAGE INFORMATION (UA)</b> .....	- 13 -
<b>THERMAL CHARACTERISTICS</b> .....	- 5 -	<b>PACKAGE INFORMATION (SO)</b> .....	- 14 -
<b>OPERATING CHARACTERISTICS</b> .....	- 6 -	<b>REVISION HISTORY</b> .....	- 15 -
<i>Electrical Characteristics</i> .....	- 6 -		


## BLOCK DIAGRAM



## ORDERING INFORMATION

Part Number	Packing	Mounting	Ambient, $T_A$	$B_{OP}(Typ.)$	$B_{RP}(Typ.)$
SC246XUA	Bulk, 1000 pieces/bag	3-pin SIP	-40°C to 150°C	±2.5mT	±1.5mT
SC246XSO	Reel, 3000pieces/reel	3-pin SOT23			
SC2464UA	Bulk, 1000 pieces/bag	3-pin SIP	-40°C to 150°C	±6.0mT	±5.0mT
SC2464SO	Reel, 3000pieces/reel	3-pin SOT23			
SC2466UA	Bulk, 1000 pieces/bag	3-pin SIP	-40°C to 150°C	±16.5mT	±13.5mT
SC2466SO	Reel, 3000pieces/reel	3-pin SOT23			

## TERMINAL CONFIGURATION



Name	Terminal Number		Type	Description
	UA	SO		
V <sub>DD</sub>	1	1	PWR	2.5V~ 24 V power supply
GND	2	3	Ground	Ground terminal
OUT	3	2	Output	Output terminal. The open drain requires a pull-up resistor

## ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted) <sup>(1)</sup>

Parameter	Symbol	Min.	Max.	Units
Power supply voltage	V <sub>DD</sub>	-28 <sup>(2)</sup>	28	V
Output terminal voltage	V <sub>OUT</sub>	-0.5	28	V
Output terminal current sink	I <sub>SINK</sub>	0	30	mA
Operating ambient temperature	T <sub>A</sub>	-40	150	°C
Maximum junction temperature	T <sub>J</sub>	-55	165	°C
Storage temperature	T <sub>STG</sub>	-65	175	°C

<sup>(1)</sup> Stresses above those listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

<sup>(2)</sup> Ensured by design.

## ESD PROTECTION

Human Body Model (HBM) tests according to: standard AEC-Q100-002 HBM

Parameter	Symbol	Min.	Max.	Units
ESD-Protection	V <sub>ESD</sub>	-4	4	KV

## THERMAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	Rating	Units
R <sub>θJA</sub>	UA Package thermal resistance	Single-layer PCB, with copper limited to solder pads	166	°C/W
R <sub>θJA</sub>	SO Package thermal resistance	Single-layer PCB, with copper limited to solder pads	228	°C/W

## OPERATING CHARACTERISTICS

### Electrical Characteristics

over operating free-air temperature range ( $V_{DD} = 5.0V$ , unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{DD}$	Operating voltage <sup>(1)</sup>	$T_J < T_{J(Max.)}$	2.5	--	24	V
$V_{DDR}$	Reverse supply voltage		-28	--	--	V
$I_{DD (off)}$	Operating supply current	$V_{DD}=2.5 \text{ to } 24 \text{ V, } T_A=25^\circ\text{C}$	1.1	1.8	2.6	mA
$I_{DD (on)}$		$V_{DD}=2.5 \text{ to } 24 \text{ V, } T_A=25^\circ\text{C}$	1.1	2.1	2.6	mA
$t_{on}$	Power-on time		--	35	50	$\mu\text{S}$
$I_{QL}$	Off-state leakage current	Output Hi-Z	--	--	1	$\mu\text{A}$
$R_{DS (on)}$	FET on-resistance	$V_{DD}=5V, I_O=10mA, T_A=25^\circ\text{C}$	--	20	--	$\Omega$
		$V_{DD}=5V, I_O=10mA, T_A=125^\circ\text{C}$	--	30	--	$\Omega$
$t_d$	Output delay time	$B=B_{RP} \text{ to } B_{OP}$	--	15	25	$\mu\text{S}$
$t_r$	Output rise time (10% to 90%)	$R1=1Kohm \text{ } Co=50pF$	--	--	0.5	$\mu\text{S}$
$t_f$	Output fall time (90% to 10%)	$R1=1Kohm \text{ } Co=50pF$	--	--	0.2	$\mu\text{S}$

(1) Maximum voltage must be adjusted for power dissipation and junction temperature, see Thermal Characteristics

## Magnetic Characteristics

over operating free-air temperature range (unless otherwise noted)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
f <sub>BW</sub>	Bandwidth		20	--	--	kHz
<b>SC2462</b>						
B <sub>OP</sub>	Operated point	T <sub>A</sub> =-40°C to 125°C	±1.5	±2.5	±3.5	mT
B <sub>RP</sub>	Release point		±1.0	±1.5	±3.0	mT
B <sub>HYS</sub>	Hysteresis		--	±1.0	--	mT
<b>SC2464</b>						
B <sub>OP</sub>	Operated point	T <sub>A</sub> =-40°C to 125°C	±4.5	±6.0	±7.5	mT
B <sub>RP</sub>	Release point		±3.5	±5.0	±6.5	mT
B <sub>HYS</sub>	Hysteresis		--	1.0	--	mT
<b>SC2466</b>						
B <sub>OP</sub>	Operated point	T <sub>A</sub> =-40°C to 125°C	±14.0	±16.5	±19.0	mT
B <sub>RP</sub>	Release point		±11.0	±13.5	±16.0	mT
B <sub>HYS</sub>	Hysteresis		--	±3.0	--	mT

1mT=10Gs


Magnetic flux density, *B*, is indicated as a negative value for North-polarity magnetic fields, and as a positive value for South-polarity magnetic fields.

## TYPICAL CHARACTERISTIC


**$I_{DD}$  vs  $V_{DD}$**




**$I_{DD}$  vs  $T_A$**



**$V_{Q(sat)}$  vs  $V_{DD}$**




**$V_{Q(sat)}$  vs  $T_A$**






## TYPICAL CHARACTERISTIC (Continued)


**SC2462 B<sub>OP</sub> and B<sub>RP</sub> vs T<sub>A</sub>**




**SC2462 B<sub>HYS</sub> vs T<sub>A</sub>**



**SC2464 B<sub>OP</sub> and B<sub>RP</sub> vs T<sub>A</sub>**



**SC2464 B<sub>HYS</sub> vs T<sub>A</sub>**



## FUNCTIONAL DESCRIPTION


The SC246X device is a chopper-stabilized Hall sensor with a digital latched output for magnetic sensing applications. The device can be powered with a supply voltage between 2.5 and 24V, and continuously survives continuous -28V reverse-battery conditions. The device does not operate when -28 to 2.2V is applied to the  $V_{DD}$  terminal (with respect to the GND terminal). In addition, the device can withstand voltages up to 40V for transient durations.

The output of SC246X switches low (turns on) when a magnetic field (South or North polarity) perpendicular to the Hall element exceeds the operate point threshold,  $B_{OP}$ . After turn-on, the output is capable of sinking 20mA and the output voltage is  $V_Q$  (sat). When the magnetic field is reduced below the release point,  $B_{RP}$ , the device output goes high (turns off). The difference in the magnetic operate and release points is the hysteresis,  $B_{HYS}$ , of the device. This built-in hysteresis allows clean switching of the output even in the presence of external mechanical vibration and electrical noise.

An external output pull-up resistor is required on the OUT terminal. The OUT terminal can be pulled up to  $V_{DD}$  or to a different voltage supply. This allows for easier interfacing with controller circuits.

## Field Direction Definition


A positive magnetic field is defined as a South pole near the marked side of the package.




## Transfer function

The SC246X exhibits “Omni polar” magnetic characteristics. It means the device reacts to both North and South magnetic pole. The purpose is to detect the presence of any magnetic field applied on the device. This mode of operation simplifies customer production processes by avoiding the need to detect the Hall sensor pole active on the magnet used in the application. Therefore, the “Omni polar” magnetic behavior helps customers by removing the need of magnet pole detection system during production phase.

Powering-on the device in the hysteresis region, less than  $B_{OP}$  and higher than  $B_{RP}$ , allows an indeterminate output state. The correct state is attained after the first excursion beyond  $B_{OP}$  or  $B_{RP}$ . If the field strength is greater than  $B_{OP}$ , then the output is pulled low. If the field strength is less than  $B_{RP}$ , the output is released.



## TYPICAL APPLICATION



The SC246X contains an on-chip voltage regulator and can operate over a wide supply voltage range. In applications that operate the device from an unregulated power supply, transient protection must be added externally. For applications using a regulated line, EMI/RFI protection may still be required. It is recommended to shunt C1 capacitors to the ground near the chip V<sub>DD</sub> power supply, with a typical value of 0.1 μF. At the same time in the external optional series resistor R1 their typical values for 100 Ω. The output capacitor C<sub>L</sub> is used as the output filter, typically 1 nF.


Select a value for C<sub>L</sub> based on the system bandwidth specifications as:

$$C_L = \frac{1}{2\pi \times R \times f \text{ (Hz)}}$$

The output stage of the SC246X device is a drain open-circuit NMOS tube, which provides a load capacity of 20mA. Adjust the pull-up resistor R<sub>L</sub> to make it work properly. The R<sub>L</sub> provides a high level for the leak-opening output. In general, less current is better, but faster transient response and bandwidth are required, with a smaller resistor R<sub>L</sub> for faster switching.

V<sub>PULL</sub> is not restricted to V<sub>DD</sub>, and could be connected to other voltage reference. The allowable voltage range of this terminal is specified in the Absolute Maximum Ratings.

## PACKAGE INFORMATION (UA)



**Notes:**





1. Exact body and lead configuration at vendor's option within limits shown.
2. Height does not include mold gate flash.

Where no tolerance is specified, dimension is nominal.

## PACKAGE INFORMATION (SO)

**3-Terminal  
SO Package**

**Dimension:mm**



**Notes:**

1. Exact body and lead configuration at vendor's option within limits shown.
2. Height does not include mold gate flash.

Where no tolerance is specified, dimension is nominal.

## REVISION HISTORY

<b>Revision</b>	<b>Date</b>	<b>Description</b>
Rev0.1	2016-08-19	Preliminary datasheet
Rev2.3	2018-05-06	The final revision of old datasheet
RevA/1.0	2020-11-19	Unified datasheet format
RevA/1.1	2024-05-07	Add SC2466

单击下面可查看定价，库存，交付和生命周期等信息

[>>Semiment \(赛卓电子\)](#)