

N-Channel Enhancement Mode MOSFET

Feature

30V/4.2A $R_{DS(ON)} = 50\text{m}\Omega(\text{MAX})$ @ $V_{GS} = 10\text{V}$.

$R_{DS(ON)} = 60\text{m}\Omega(\text{MAX})$ @ $V_{GS} = 4.5\text{V}$.


Super High dense cell design for extremely low $R_{DS(ON)}$.

Reliable and Rugged.

SC-59 for Surface Mount Package.



SC-59



Marking: A2PA

Applications

- Power Management

Portable Equipment and Battery Powered Systems.

Absolute Maximum Ratings

$T_A=25^\circ\text{C}$ Unless Otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 12	V
Drain Current-Continuous	I_D	4.2	A





Electrical Characteristics

$T_A=25^\circ\text{C}$ Unless Otherwise noted

Parameter	Symbol	Test Conditions	Min	Typ.	Max	Units
Off Characteristics						
Drain to Source Breakdown Voltage	$BVDSS$	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	30	-	-	V
Zero-Gate Voltage Drain Current	$IDSS$	$V_{DS}=30\text{V}, V_{GS}=0\text{V}$	-	-	1	μA
Gate Body Leakage Current, Forward	$IGSSF$	$V_{GS}=12\text{V}, V_{DS}=0\text{V}$	-	-	100	nA
Gate Body Leakage Current, Reverse	$IGSSR$	$V_{GS}=-12\text{V}, V_{DS}=0\text{V}$	-	-	-100	nA
On Characteristics						
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{GS}=V_{DS}, I_D=250\mu\text{A}$	0.6	-	2.5	V
Static Drain-source On-Resistance	$R_{DS(\text{ON})}$	$V_{GS}=10\text{V}, I_D=4\text{A}$	-	48	50	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}, I_D=3\text{A}$	-	55	60	$\text{m}\Omega$
		$V_{GS}=2.5\text{V}, I_D=2\text{A}$	-	60	65	$\text{m}\Omega$
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0\text{V}, I_S=1.25\text{A}$			1.2	V

Dynamic

Q _g	Total Gate Charge	V _{DS} =15V,V _{GS} =10V,I _D =2A	8.5	12	nC
Q _{gs}	Gate-Source Charge		1.1		
Q _{gd}	Gate-Drain Charge		1.8		
t _{on}	Turn-on Time	V _{DD} =15V,I _D =2A,V _{GS} =10V,R _G =6Ω		40	ns
t _{d(ON)}	Turn-on Delay time			11	
t _r	Turn-on Rise Time			17	
T _{d(off)}	Turn-off Delay Time			37	
t _f	Turn-off Fall Time			20	
t _{off}	Turn-off Time			60	

Typical Characteristics

Figure 1 . Output Characteristics

Figure 2 . Transfer Characteristics
Typical Characteristics

Figure 3 . Gate Threshold Variation with Temperature

Figure 4 . On-Resistance Variation with Temperature




Figure 5 . On-Resistance vs. Gate-to-Source Voltage





Figure 6 . Source-Drain Diode Forward Voltage

Package Outline Dimensions (UNIT: mm)



单击下面可查看定价，库存，交付和生命周期等信息

[>>SHIKUES\(时科\)](#)