



## 20V Single N-Channel Enhancement-Mode MOSFET

General Description	Product Summary	
• Low gate charge.	$\bullet \text{BV}_{\text{DSS}}$	20V
• Use as a load switch.	$\bullet R_{\text{DS(on)}} @ V_{\text{GS}} = 4.5\text{V}$	$< 28\text{m}\Omega$
• Use in PWM applications	$\bullet R_{\text{DS(on)}} @ V_{\text{GS}} = 2.5\text{V}$	$< 38\text{m}\Omega$

SOT-23



### Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{\text{DS}}$	20	V
Gate-Source Voltage	$V_{\text{GS}}$	$\pm 12$	V
Drain Current ( $T_A=25^\circ\text{C}$ )	$I_D$	5.4	A
Drain Current ( $T_A=75^\circ\text{C}$ )		2.8	A
Pulsed Drain Current <sup>a</sup>	$I_{\text{DM}}$	20	A
Power Dissipation <sup>b</sup> ( $T_A=25^\circ\text{C}$ )	$P_D$	1.25	W
Power Dissipation <sup>b</sup> ( $T_A=75^\circ\text{C}$ )		1.0	W
Junction and Storage Temperature Range	$T_J, T_{\text{STG}}$	-55 ~ +150	°C


### Thermal Characteristics

Parameter	Symbol	Maximum	Units
Junction-to-Ambient <sup>a</sup> ( $t \leq 10\text{s}$ )	$R_{\theta JA}$	100	°C/W
Junction-to-Ambient <sup>a,d</sup> (Steady-State)		130	°C/W
Junction-to-Lead (Steady-State)	$R_{\theta JL}$	90	°C/W

<b>Electrical Characteristics (<math>T_A = 25^\circ\text{C}</math> unless otherwise noted)</b>						
<b>Symbol</b>	<b>Parameter</b>	<b>Conditions</b>	<b>Min</b>	<b>Typ</b>	<b>Max</b>	<b>Units</b>
<b>Off Characteristics</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0\text{V}$ , $I_D = 250\mu\text{A}$	20			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 20\text{V}$ , $V_{\text{GS}} = 0\text{V}$			1	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body Leakage Current	$V_{\text{GS}} = \pm 8\text{V}$ , $V_{\text{DS}} = 0\text{V}$			$\pm 100$	nA
<b>On Characteristics</b>						
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}$ , $I_D = 250\mu\text{A}$	0.5		1.2	V
$R_{\text{DS(ON)}}$	Drain-Source On-State Resistance	$V_{\text{GS}} = 4.5\text{V}$ , $I_D = 5.4\text{A}$		22	28	$\text{m}\Omega$
		$V_{\text{GS}} = 2.5\text{V}$ , $I_D = 4.5\text{A}$		28	38	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{\text{DS}} = 2.5\text{V}$ , $I_D = 5.4\text{A}$		20		S
<b>Drain-Source Diode Characteristics</b>						
$V_{\text{SD}}$	Diode Forward Voltage	$V_{\text{GS}} = 0\text{V}$ , $I_S = 1.0\text{A}$			1.2	V
$I_S$	Maximum Body-Diode Continuous Current				2.0	A
<b>Dynamic Characteristics</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{\text{DS}} = 15\text{V}$ , $V_{\text{GS}} = 0\text{V}$ $f = 1.0\text{MHz}$		380		pF
$C_{\text{oss}}$	Output Capacitance			52		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			35		pF
$Q_g$	Total Gate Charge	$V_{\text{DS}} = 15\text{V}$ , $I_D = 5.4\text{A}$ $V_{\text{GS}} = 4\text{V}$		8.5		nC
$Q_{\text{gs}}$	Gate-Source Charge			1.5		nC
$Q_{\text{gd}}$	Gate-Drain Charge			1.1		nC
$t_{\text{D(ON)}}$	Turn-On Delay Time	$V_{\text{DD}} = 15\text{V}$ , $I_D = 1\text{A}$ $V_{\text{GS}} = 4\text{V}$ $R_{\text{GEN}} = 6 \text{ ohm}$		12		ns
$t_r$	Turn-On Rise Time			17		ns
$t_{\text{D(OFF)}}$	Turn-Off Delay Time			18		ns
$t_f$	Turn-Off Fall Time			14		ns

- a. Repetitive rating, Pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ . Ratings are based on low frequency and duty cycles to keep initial  $T_J=25^\circ\text{C}$
- b. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=150^\circ\text{C}$ , using  $\leq 10\text{s}$  junction-to-ambient thermal resistance.
- c. The value of  $R_{\theta_{JA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A = 25^\circ\text{C}$ . The value in any given application depends on the user's specific board design.
- d. The  $R_{\theta_{JA}}$  is the sum of the thermal impedance from junction to lead  $R_{\theta_{JL}}$  and lead to ambient.

## SOT-23 Package Outline



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.	0.022 REF.		
theta	0.300	0.500	0.012	0.020

单击下面可查看定价，库存，交付和生命周期等信息

>>[SiliconWisdom\(矽睿半导体\)](#)