


Multilayer Chip Power Inductor – MPL Series

Operating Temp. : -40°C~+85°C



FEATURES

- High DC bias current due to developed material
- Low DC resistance
- Low profile and thin thickness
- Monolithic structure for high reliability
- Excellent solderability and high heat resistance
- No cross coupling due to magnetic shield

APPLICATIONS

- DC-DC converter circuits for mobile phones, DSCs, DVCs, HDDs, PDAs, etc.

PRODUCT IDENTIFICATION

<u>MPL</u>	<u>2012</u>	<u>S</u>	<u>2R2</u>	<u>M</u>	<u>H</u>	<u>I</u>																				
①	②	③	④	⑤	⑥	⑦																				
①	②		④		⑥																					
<table border="1"> <tr><th colspan="2">Type</th></tr> <tr><td>MPL</td><td>Chip Power Inductor</td></tr> </table>	Type		MPL	Chip Power Inductor	<table border="1"> <tr><th colspan="2">External Dimensions (L×W) (mm)</th></tr> <tr><td>1608 [0603]</td><td>1.6×0.8</td></tr> <tr><td>2012 [0805]</td><td>2.0×1.25</td></tr> <tr><td>2016 [0806]</td><td>2.0×1.6</td></tr> <tr><td>2520 [1008]</td><td>2.5×2.0</td></tr> </table>		External Dimensions (L×W) (mm)		1608 [0603]	1.6×0.8	2012 [0805]	2.0×1.25	2016 [0806]	2.0×1.6	2520 [1008]	2.5×2.0	<table border="1"> <tr><th colspan="2">Nominal Inductance</th></tr> <tr><th>Example</th><th>Nominal Value</th></tr> <tr><td>R47</td><td>0.47μH</td></tr> <tr><td>4R7</td><td>4.7μH</td></tr> </table>		Nominal Inductance		Example	Nominal Value	R47	0.47μH	4R7	4.7μH
Type																										
MPL	Chip Power Inductor																									
External Dimensions (L×W) (mm)																										
1608 [0603]	1.6×0.8																									
2012 [0805]	2.0×1.25																									
2016 [0806]	2.0×1.6																									
2520 [1008]	2.5×2.0																									
Nominal Inductance																										
Example	Nominal Value																									
R47	0.47μH																									
4R7	4.7μH																									
③	⑤		⑦		⑥																					
<table border="1"> <tr><th colspan="2">Feature Type</th></tr> <tr><td>S</td><td rowspan="3">(Internal Code)</td></tr> <tr><td>L</td></tr> <tr><td>C</td></tr> </table>	Feature Type		S	(Internal Code)	L	C	<table border="1"> <tr><th colspan="2">Inductance Tolerance</th></tr> <tr><td>M</td><td>±20%</td></tr> <tr><td>N</td><td>±30%</td></tr> </table>		Inductance Tolerance		M	±20%	N	±30%	<table border="1"> <tr><th colspan="2">Thickness</th></tr> <tr><td>D</td><td>0.5mm</td></tr> <tr><td>H</td><td>0.9mm</td></tr> <tr><td>W</td><td>1.1mm</td></tr> <tr><td>Y</td><td>1.25mm</td></tr> </table>		Thickness		D	0.5mm	H	0.9mm	W	1.1mm	Y	1.25mm
Feature Type																										
S	(Internal Code)																									
L																										
C																										
Inductance Tolerance																										
M	±20%																									
N	±30%																									
Thickness																										
D	0.5mm																									
H	0.9mm																									
W	1.1mm																									
Y	1.25mm																									
⑦	⑤		⑦		⑥																					
<table border="1"> <tr><th colspan="2">Packing</th></tr> <tr><td>T</td><td>Tape & Reel</td></tr> </table>	Packing		T	Tape & Reel	<table border="1"> <tr><th colspan="2">Inductance Tolerance</th></tr> <tr><td>M</td><td>±20%</td></tr> <tr><td>N</td><td>±30%</td></tr> </table>		Inductance Tolerance		M	±20%	N	±30%	<table border="1"> <tr><th colspan="2">Thickness</th></tr> <tr><td>D</td><td>0.5mm</td></tr> <tr><td>H</td><td>0.9mm</td></tr> <tr><td>W</td><td>1.1mm</td></tr> <tr><td>Y</td><td>1.25mm</td></tr> </table>		Thickness		D	0.5mm	H	0.9mm	W	1.1mm	Y	1.25mm		
Packing																										
T	Tape & Reel																									
Inductance Tolerance																										
M	±20%																									
N	±30%																									
Thickness																										
D	0.5mm																									
H	0.9mm																									
W	1.1mm																									
Y	1.25mm																									

SHAPE AND DIMENSIONS

Unit: mm [inch]

Type	L	W	T	a
1608 [0603]	1.6±0.15 [.063±.006]	0.8±0.15 [.031±.006]	0.5±0.1 [.020±.004]	0.3±0.2 [.012±.008]
			0.8±0.15 [.031±.006]	
2012 [0805]	2.0 (+0.3, -0.1) [.079 (+.012, -.004)]	1.25±0.2 [.049±.008]	0.5±0.1 [.020±.004]	0.5±0.3 [.020±.012]
			0.9±0.1 [.035±.004]	
			1.25±0.2 [.049±.008]	
2016 [0806]	2.0 (+0.3, -0.1) [.079 (+.012, -.004)]	1.6±0.2 [.063±.008]	0.9±0.1 [.035±.004]	0.5±0.3 [.020±.012]
2520 [1008]	2.5±0.2 [.098±.008]	2.0 (+0.3, -0.1) [.079 (+.012, -.004)]	0.9±0.1 [.035±.004]	0.5±0.3 [.020±.012]
			1.1±0.1 [.043±.004]	

SPECIFICATIONS

MPL1608 TYPE

Part Number	Inductance	L Test Freq.	Min. Self-resonant Frequency	DC Resistance	Max. Rated Current	Thickness
Units	μH	MHz	MHz	Ω	mA	mm [inch]
Symbol	L	Freq.	S.R.F	DCR	Ir*	T
MPL1608SR47□DT	0.47	5	105	0.19±25%	900	0.5±0.1 [.020±.004]
MPL1608LR47□HT	0.47	5	105	0.12±25%	1200	0.8±0.15 [.031±.006]
MPL1608SR47□HT	0.47	5	105	0.25±25%	800	
MPL1608SR68□HT	0.68	5	90	0.16±25%	1000	
MPL1608S1R0□HT	1.0	1	75	0.20±25%	950	
MPL1608S1R5□HT	1.5	1	50	0.25±25%	800	
MPL1608S2R2□HT	2.2	1	40	0.30±25%	750	

MPL2012 TYPE

Part Number	Inductance	L Test Freq.	Min. Self-resonant Frequency	DC Resistance	Max. Rated Current	Thickness
Units	μH	MHz	MHz	Ω	mA	mm [inch]
Symbol	L	Freq.	S.R.F	DCR	Ir*	T
MPL2012SR47□DT	0.47	1	100	0.12±25%	1100	0.5±0.1 [.020±.004]
MPL2012S1R0□DT	1.0	1	60	0.19±25%	800	
MPL2012S1R5□DT	1.5	1	50	0.26±25%	700	
MPL2012S2R2□DT	2.2	1	40	0.34±25%	600	
MPL2012SR47□HT	0.47	1	100	0.09±25%	1200	0.9±0.1 [.035±.004]
MPL2012S1R0□HT	1.0	1	60	0.11±25%	1000	
MPL2012S1R5□HT	1.5	1	50	0.16±25%	900	
MPL2012S2R2□HT	2.2	1	40	0.25±25%	800	
MPL2012S3R3□HT	3.3	1	30	0.19±25%	900	
MPL2012S4R7□HT	4.7	1	30	0.25±25%	800	
MPL2012C2R2□HT	2.2	1	40	0.45±25%	500	
MPL2012S2R2□YT	2.2	1	40	0.33±30%	640	
MPL2012S4R7□YT	4.7	1	25	0.50±30%	600	1.25±0.2 [.049±.008]

MPL2016 TYPE

Part Number	Inductance	L Test Freq.	Min. Self-resonant Frequency	DC Resistance	Max. Rated Current	Thickness
Units	μH	MHz	MHz	Ω	mA	mm [inch]
Symbol	L	Freq.	S.R.F	DCR	Ir*	T
MPL2016SR47□HT	0.47	1	100	0.06±25%	1600	0.9±0.1 [.035±.004]
MPL2016S1R0□HT	1.0	1	70	0.09±25%	1400	
MPL2016S1R5□HT	1.5	1	60	0.11±25%	1200	
MPL2016S2R2□HT	2.2	1	50	0.11±25%	1200	
MPL2016S3R3□HT	3.3	1	40	0.12±25%	1200	
MPL2016S4R7□HT	4.7	1	30	0.14±25%	1100	

SPECIFICATIONS

MPL2520 TYPE


Part Number	Inductance	L Test Freq.	Min. Self-resonant Frequency	DC Resistance	Max. Rated Current	Thickness
Units	μH	MHz	MHz	Ω	mA	mm [inch]
Symbol	L	Freq.	S.R.F	DCR	I_r^*	T
MPL2520SR47□HT	0.47	1	100	0.04±25%	1800	0.9±0.1 [.035±.004]
MPL2520S1R0□HT	1.0	1	60	0.06±25%	1600	
MPL2520S1R5□HT	1.5	1	50	0.07±25%	1500	
MPL2520S2R2□HT	2.2	1	40	0.08±25%	1300	
MPL2520S3R3□HT	3.3	1	30	0.10±25%	1200	
MPL2520S4R7□HT	4.7	1	25	0.11±25%	1100	
MPL2520S1R0□WT	1.0	1	70	0.09±25%	1500	1.1±0.1 [.043±.004]
MPL2520S2R2□WT	2.2	1	40	0.12±25%	1000	
MPL2520S3R3□WT	3.3	1	30	0.12±25%	1000	
MPL2520S4R7□WT	4.7	1	25	0.14±25%	900	
MPL2520S100□WT	10	1	15	0.30±30%	800	

※□: Please specify the inductance tolerance code (M=±20%, N=±30%).




※ I_r^* : DC current causes temperature rise of 40°C from 20°C ambient

TYPICAL ELECTRICAL CHARACTERISTICS

Inductance vs. Frequency Characteristics




Inductance vs. DC Current Characteristics






TYPICAL ELECTRICAL CHARACTERISTICS

Inductance vs. Frequency Characteristics



Inductance vs. DC Current Characteristics



单击下面可查看定价，库存，交付和生命周期等信息

[>>SL\(顺络\)](#)