

High Efficiency, Synchronous 32V/2A Buck Converter

1 Descriptions

SC8109 is a synchronous buck converter with a wide input voltage from 4.4V to 32V. The SC8109 regulates the output voltage at a fixed 5.1V or customized voltage by setting the divider resistor. It also provides high accurate output current limit. The converter enters Constant Current (CC) Mode in case the output reaches the setting current limit. The total output power can be programmed by a resistor, which makes it easy for constant power (CP) control.

SC8109 integrates 45mΩ high side NMOS and 30mΩ low side NMOS to achieve high efficiency. Besides, it provides low side gate driver (LSD) to drive external NMOS and works with build-in NMOS.

SC8109 adopts programmable line drop compensation, programmable frequency setting with minimum external components, maximum functions can be achieved for user's different applications.

SC8109 also supports full protections including under voltage protection, over voltage protection, short current protection and auto-restart, over temperature protection.

SC8109 adopts 19 pin QFN 3x3 package.

3 Applications

- Car Charger
- USB Power supplies with PD or Fast charge
- MFP Power Supply
- Industrial applications

2 Features

- Wide input operating voltage from 4.4V to 32V
- Max output capacity 5V/2A with internal MOSFETs
- External low side NMOS gate driver
- Almost 100% duty cycle operation
- Ultra-low quiescent current
- $\pm 2\%$ output voltage reference accuracy
- $\pm 4.5\%$ output current limit accuracy
- Programmable output power limit
- Programmable line drop compensation
- PFM mode
- Fixed-150K switching frequency or adjustable by external resistor
- Hiccup and auto-restart
- Full protection of UVLO, IN/OUT-OVP, OCP, OTP
- Available in QFN-19 3x3 Package

4 Device Information

ORDER NUMBER	PACKAGE	BODY SIZE
SC8109QFKR	19 pin QFN	3mm x 3mm x 0.55mm

单击下面可查看定价，库存，交付和生命周期等信息

[>>SOUTHCHIP\(南芯\)](#)