

# STARPOWER

SEMICONDUCTOR

# IGBT

## GD100HFU120C1S

Molding Type Module

**1200V/100A 2 in one-package**


### General Description

STARPOWER IGBT Power Module provides ultrafast switching speed as well as short circuit ruggedness. It's designed for the applications such as electronic welder and inductive heating.



### Features

- NPT IGBT technology
- 10 $\mu$ s short circuit capability
- Low switching losses
- Rugged with ultrafast performance
- $V_{CE(sat)}$  with positive temperature coefficient
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology



Equivalent Circuit Schematic

### Typical Applications

- Switching mode power supplies
- Inductive heating
- Electronic welder

**Absolute Maximum Ratings**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Description	GD100HFU120C1S	Units
$V_{CES}$	Collector-Emitter Voltage	1200	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^\circ\text{C}$	170	A
	@ $T_C=80^\circ\text{C}$	100	
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	200	A
$I_F$	Diode Continuous Forward Current	100	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	200	A
$P_D$	Maximum Power Dissipation @ $T_j=150^\circ\text{C}$	679	W
$T_{jmax}$	Maximum Junction Temperature	150	$^\circ\text{C}$
$T_{jop}$	Operating Junction Temperature	-40 to +125	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^\circ\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$	2500	V
Mounting Torque	Power Terminal Screw:M5 Mounting Screw:M6	2.5 to 5.0 3.0 to 5.0	N.m

**Electrical Characteristics of IGBT**  $T_C=25^\circ\text{C}$  unless otherwise noted**Off Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^\circ\text{C}$	1200			V
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA

**On Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	4.4	4.9	6.0	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=100\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		3.10	3.55	V
		$I_C=100\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		3.45		

## Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=100A,$ $R_G=5.6\Omega, V_{GE}=\pm 15V,$ $T_j=25^\circ C$		300		ns
$t_r$	Rise Time			64		ns
$t_{d(off)}$	Turn-Off Delay Time			340		ns
$t_f$	Fall Time			105		ns
$E_{on}$	Turn-On Switching Loss			4.76		mJ
$E_{off}$	Turn-Off Switching Loss			4.25		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=100A,$ $R_G=5.6\Omega, V_{GE}=\pm 15V,$ $T_j=125^\circ C$		320		ns
$t_r$	Rise Time			65		ns
$t_{d(off)}$	Turn-Off Delay Time			350		ns
$t_f$	Fall Time			13		ns
$E_{on}$	Turn-On Switching Loss			7.20		mJ
$E_{off}$	Turn-Off Switching Loss			5.50		mJ
$C_{ies}$	Input Capacitance	$V_{CE}=30V, f=1MHz,$ $V_{GE}=0V$		8.45		nF
$C_{oes}$	Output Capacitance			0.76		nF
$C_{res}$	Reverse Transfer Capacitance			0.31		nF
$I_{SC}$	SC Data	$t_p \leq 10\mu s, V_{GE}=15V,$ $T_j=125^\circ C, V_{CC}=600V,$ $V_{CEM} \leq 1200V$		900		A
$R_{Gint}$	Internal Gate Resistance			/		$\Omega$
$L_{CE}$	Stray Inductance				30	nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal To Chip			0.75		m $\Omega$

Electrical Characteristics of Diode  $T_C=25^\circ C$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_F=100A,$ $V_{GE}=0V$	$T_j=25^\circ C$	1.82	2.22	V
			$T_j=125^\circ C$	1.95		
$Q_r$	Recovered Charge	$I_F=100A,$ $V_R=600V,$ $R_G=5.6\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$	5.4		$\mu C$
			$T_j=125^\circ C$	11.2		
$I_{RM}$	Peak Reverse Recovery Current	$V_{GE}=-15V$	$T_j=25^\circ C$	81		A
			$T_j=125^\circ C$	101		
$E_{rec}$	Reverse Recovery Energy	$V_{GE}=-15V$	$T_j=25^\circ C$	3.54		mJ
			$T_j=125^\circ C$	6.57		

**Thermal Characteristics**

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case (per IGBT)		0.184	K/W
$R_{\theta JC}$	Junction-to-Case (per Diode)		0.300	K/W
$R_{\theta CS}$	Case-to-Sink (Conductive grease applied)	0.05		K/W
Weight	Weight of Module	150		g




Fig 1. IGBT Output Characteristic




Fig 2. IGBT Transfer Characteristic




Fig 3. IGBT Switching Loss vs.  $I_C$




Fig 4. IGBT Switching Loss vs.  $R_G$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristic




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$





Fig 10. Diode Transient Thermal Impedance

**Package Dimensions**

Dimensions in Millimeters





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.

单击下面可查看定价，库存，交付和生命周期等信息

[>>STARPOWER\(斯达\)](#)