

# DATA SHEET

SUNGMUN CODE : BSI-10H

DESCRIPTION : MINI SLIDE SWITCH

## SUNGMUN ELECTRONICS CO., LTD.

Address 301-302, Bucheon Technopark 345, Seokcheon-ro, Ojeong-gu  
Bucheon-si, Gyeonggi-do, Korea

TEL. +82-32-328-1941~4

FAX +82-32-328-1945

E-mail [sungmun@sungmun.co.kr](mailto:sungmun@sungmun.co.kr)








Website [www.sungmun.com](http://www.sungmun.com)




MRK.	DATE	REVISION	SIGN
△			

## SPECIFICATION

1. Rating : DC12V 0.5A~24V 0.3A.
2. Contact Resistance : 30mΩ Max.
3. Travel : 1.6mm.
4. Operating Force : 250 ± 150gf.
5. Life Cycle : 2,000 Cycle (with load).
6. Packing : 200pcs Vinyl Bag



DRAWN/DESIGNED	CHECKED	APPROVED	G.TOL ±0.3	TITLE MINI SLIDE SWITCH
Y.S KIM	BS KANG	K.I LEE		
2021-08-23	2021-08-23	2021-08-24	UNIT mm	MODEL NO. BSI-10H
 <b>SUNGMUN ELECTRONICS CO.,LTD</b>			SCALE 3:1	DRAW NO. BSI-10H-03
			SIZE A4	REV. 03

### 1. Electrical Characteristics :

- 1-1 Rating : AC, DC 12V 0.5A ~ 24V 0.3A (Minimum current: 1mA)
- 1-2 Contact Resistance : Max 30mΩ
- 1-3 Insulation Resistance : Min 10,000 MΩ at DC 500V
- 1-4 Withstanding Voltage : 1min at AC 500V

### 2. Mechanical Characteristics :

- 2-1 Operating Force : 250 ± 150gf
- 2-2 Travel : 1.6mm
- 2-3 Insulator :
  - 2-3-1 Case : Glass Fiber resin
  - 2-3-2 Slide : Glass Fiber resin
- 2-4 Terminal : Nickel, Gold Plate

### 3. Life Test :

- 3-1 Test Condition : Operations at a rate of 15-20 cycles in 1 minute
  - 3-1-1 With load : 2,000 cycles
  - 3-1-2 Without load : 10,000 cycles
- 3-2 Operating Force : With +40%, -40% of Initial Value
- 3-3 Contact Resistance : Max 200mΩ

### 4. Environmental Characteristics :

- 4-1 Operating Temperature : -40°C to +85°C
- 4-2 Storage Temperature : -40°C to +85°C
- 4-3 Humidity Test :
  - 4-3-1 Test Conditions : Measured 1 hour after exposure to ambient  
After 96 hours exposure at 40±2°C, 90-95%R.H
  - 4-3-2 Insulation Resistance : Min 100 MΩ at DC 500V
  - 4-3-3 Withstanding Voltage : 1 min at AC 250V

### 5. Solder Conditions :

- 5-1 Hand Solder : 3~4 sec. at 350°C
- 5-2 Wave Solder : 5 sec. at 260°C

单击下面可查看定价，库存，交付和生命周期等信息

[>>SUNGMUN\(韩国星纹电子\)](#)