



**VOLTAGE RANGE: 20 - 100V**  
**CURRENT: 3.0 A**

### Features

- Schottky Barrier Chip
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- For Use in Low Voltage Application
- Guard Ring Die Construction
- Plastic Case Material has UL Flammability Classification Rating 94V-O

### Mechanical Data

- Case: SMB/DO-214AA, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.093 grams (approx.)









SMB(DO-214AA)		
Dim	Min	Max
A	3.30	3.94
B	4.06	4.70
C	1.91	2.21
D	0.15	0.31
E	5.00	5.59
G	0.10	0.20
H	0.76	1.52
J	2.00	2.62
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	B320B	B330B	B340B	B350B	B360B	B380B	B390B	B3100B	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>									
Working Peak Reverse Voltage	V <sub>RWM</sub>	20	30	40	50	60	80	90	100	V
DC Blocking Voltage	V <sub>R</sub>									
RMS Reverse Voltage	V <sub>R(RMS)</sub>	14	21	28	35	42	56	64	71	V
Average Rectified Output Current @T <sub>L</sub> = 105°C	I <sub>o</sub>	3.0								A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	80								A
Forward Voltage @I <sub>F</sub> = 2.0A	V <sub>FM</sub>	0.55		0.70		0.85				V
Peak Reverse Current @T <sub>A</sub> = 25°C	I <sub>RM</sub>	1.0								mA
At Rated DC Blocking Voltage @T <sub>A</sub> = 100°C		20								
Typical Thermal Resistance (Note 1)	R <sub>θJL</sub> R <sub>θJA</sub>	10 50								°C/W
Operating Temperature Range	T <sub>j</sub>	-65 to +125								°C
Storage Temperature Range	T <sub>STG</sub>	-65 to +150								°C

## RATINGS AND CHARACTERISTIC CURVES B320B THRU B3100B



单击下面可查看定价，库存，交付和生命周期等信息

[>>SUNMATE\(森美特\)](#)