

VOLTAGE RANGE: 20 - 100V





CURRENT: 1.0 A

Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High forward surge current capability
- High temperature soldering guaranteed:
250°C/10 seconds, 0.375(9.5mm) lead length,
5 lbs. (2.3kg) tension

Mechanical Data

- Case: JEDEC SOD-123FL molded plastic body over passivated junction
- Terminals: Plated axial leads,
- solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- Weight: 0.0007 ounce, 0.02 grams



SOD-123FL			
Dim	Min	Max	Typ
A	3.58	3.72	3.65
B	2.72	2.78	2.75
C	1.77	1.83	1.80
D	1.02	1.08	1.05
E	0.097	1.03	1.00
H	0.13	0.17	0.15
L	0.53	0.57	0.55
All Dimensions in mm			





Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	SS1020FL	SS1030FL	SS1040FL	SS1060FL	SS1080FL	SS10100FL	Unit
	Marking	S2	S3	S4	S6	S8	SA	
Maximum recurrent peak reverse voltage	V _{RRM}	20	30	40	60	80	100	V
Maximum RMS voltage	V _{RMS}	14	21	28	42	56	70	V
Maximum DC blocking voltage	V _{DC}	20	30	40	60	80	100	V
Maximum average forward rectified current T _j =90	I _(AV)	1.0						A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I _{FSM}	20						A
Maximum instantaneous @I _{FM} =1.0A forward voltage	V _F	0.50	0.55		0.72	0.85		V
Repetitive peak reverse current at rated DC blocking voltage	I _R	0.3						mA
Typical junction capacitance	C _J	30						p F
Operating temperature range	T _j	- 55 --- + 125						
Storage temperature range	T _{STG}	- 55 --- + 150						

NOTE1. Measured at f=1.0MHz, V_R=4.0V

RATINGS AND CHARACTERISTIC CURVES SS1020FL THRU SS10100FL



单击下面可查看定价，库存，交付和生命周期等信息

[>>SUNMATE\(森美特\)](#)