


VOLTAGE RANGE: 40V
CURRENT: 0.03A


Features

- High current rectifier schottky diode.
- Low voltage;Low inductance.
- For power supply.



Mechanical Data

- Case: SOD-323, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.004 grams (approx.)
- Marking: B 4



SOD-323		
Dim	Min	Max
A	2.30	2.70
B	1.75	1.95
C	1.15	1.35
D	0.25	0.35
E	0.05	0.15
G	0.70	0.95
H	0.30	—
All Dimensions in mm		

Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Limits	Unit
Peak reverse voltage	V_{RM}	40	V
DC reverse voltage	V_R	30	V
Mean rectifying current	I_O	0.03	A
Peak forward surge current	I_{FSM}	0.2	A
Junction temperature	T_j	125	$^\circ\text{C}$
Storage temperature	T_{stg}	-40~+125	$^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V_F			0.37	V	$I_F=1\text{mA}$
Reverse current	I_R			0.5	μA	$V_R=30\text{V}$
Capacitance between terminals	C_T		2		pF	$V_R=1\text{V}, f=1\text{MHz}$

单击下面可查看定价，库存，交付和生命周期等信息

[>>SUNMATE\(森美特\)](#)