

**Features**

- Low driver power requirements (TTL/CMOS Compatible)
- No moving parts
- High reliability
- Arc-Free with no snubbing circuits
- 3750Vrms Input/Output isolation

**Applications**


- Telecommunications (PC, Electronic notepad)
- Measuring and Testing equipment
- Industrial control
- Security equipments
- High speed inspection machine

**Outline Dimensions**

DIP4



SMD4



1. LED Anode
2. LED Cathode
- 3, 4. Drain (MOS FET)

**TYPES**


Category	Output rating		Package	Part No.	Packing quantity
	Load voltage	Load current			
AC/DC	60V	2.5A	DIP4	GAQY252G3E	50pcs/tube
			SMD4	GAQY252G3EH	1000pcs/1reel

**Absolute Maximum Ratings (Ambient Temperature: 25°C)**

Item	Symbol	Value	Units	Note
Input	Continuous LED Current	I <sub>F</sub>	50	mA
	Peak LED Current	I <sub>FP</sub>	1000	mA
	LED Reverse Voltage	V <sub>R</sub>	5	V
	Input Power Dissipation	P <sub>In</sub>	75	mW
Output	Load Voltage	V <sub>L</sub>	60	V(AC peak or DC)
	Load Current	I <sub>L</sub>	2.5	A
	Peak Load Current	I <sub>Peak</sub>	5.0	A
	Output Power Dissipation	P <sub>out</sub>	400	mW
Total Power Dissipation	P <sub>T</sub>	500	mW	
I/O Breakdown Voltage	V <sub>I/O</sub>	1500	Vrms	RH=60%, 1min
Operating Temperature	T <sub>opr</sub>	-40 to +85	°C	
Storage Temperature	T <sub>stg</sub>	-40 to +100	°C	
Pin Soldering Temperature	T <sub>sol</sub>	260	°C	10 sec max.








## Electrical Specifications (Ambient Temperature: 25°C)

Item		Symbol	MIN.	TYP.	MAX.	Units	Conditions
Input	LED Forward Voltage	$V_F$		1.2	1.4	V	$I_F=10\text{mA}$
	Operation LED Current	$I_{F\text{ on}}$		0.5	3.0	mA	
	Recovery LED Current	$I_{F\text{ off}}$		0.35	0.5	mA	
	Recovery LED Voltage	$V_{F\text{ off}}$	0.7			V	
Output	On-Resistance	$R_{on}$		0.06	0.1	$\Omega$	$I_F=5\text{mA}, I_L=100\text{mA},$ Time to flow is within 1 sec.
	Off-State Leakage Current	$I_{\text{Leak}}$			1	$\mu\text{A}$	$V_L=\text{Rating}$
	Output Capacitance	$C_{out}$		190		pF	$V_L=0, f=1\text{MHz}$
Transmission	Turn-On Time	$T_{on}$		1.5	3.0	ms	$I_F=5\text{mA}, I_L=100\text{mA},$
	Turn-Off Time	$T_{off}$		0.1	0.3	ms	
Coupled	I/O Isolation Resistance	$R_{i/o}$	$10^{10}$			$\Omega$	DC500V
	I/O Capacitance	$C_{i/o}$		0.8	1.5	pF	$f=1\text{MHz}$








Please obey the following conditions to ensure proper device operation and resetting. Input LED current (Recommended value):  $I_F \geq 5\text{mA}$  and  $\leq 30\text{mA}$ . Examples of resistance value to control LED forward current ( $I_F=5\text{mA}$ , INPUT VOLTAGE="E", RESISTORS="R")  
 $E=3.3V, R=330\Omega; E=5V, R=640\Omega; E=12V, R=1.9K\Omega; E=15V, R=2.5K\Omega; E=24V, R=4.1K\Omega;$

## Reference Data



Voltage Vs. current characteristics  
of output at MOS portion




#### Dimensions

##### 4-SMD





##### Dimensions

mm inch




##### Surface mount terminal type



Terminal thickness =  
0.2 .008



General tolerance:  $\pm 0.1 \pm .004$

PC board pattern (Top view)




Unit : mm [inch]  
Tolerance :  $\pm 0.1$

Tape dimensions



Dimensions of tape reel




Unit: mm

TYPE	$Bo \pm 0.1$	$F_0 \pm 0.1$	$W_0 \pm 0.1$	13"REEL/PCS
4P	5.3	7.5	16	1000

## Dimensions


4-DIP



mm inch


Dimensions

Through hole terminal type



PC board pattern


(TOP VIEW)



Unit : mm inch  
Tolerance: +0.2 -.007

DIP type

Devices are packaged in a tube so that pin No. 1 is on the stopper B side. Observe correct orientation when mounting them on PC boards.



单击下面可查看定价，库存，交付和生命周期等信息

[>>SUPSiC\(国晶微\)](#)