



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## Product Specifications Approval Sheet

Product Description: SAW Filter 2492 MHz SMD 3.0x3.0 mm (BW=8 MHz)

TST Part No.: TA2220A

Customer Part No.: \_\_\_\_\_

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: \_\_\_\_\_ David Chang *David*

Approved by: \_\_\_\_\_ Andy Yu *Andy Yu*

Date: \_\_\_\_\_ 2017/07/18

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## SAW Filter 2492 MHz

MODEL NO.: TA2220A

REV. NO.:1

### A. MAXIMUM RATING:

1. Input Power Level: 10 dB<sub>m</sub>
2. DC voltage: 3 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant  
Lead free  
Lead-free soldering

Electrostatic Sensitive Device (ESD)


### B. ELECTRICAL CHARACTERISTICS:

Temperature range for specification: 25°C




Item	Unit	Min.	Typ.	Max.
<b>Center frequency</b> <b>F<sub>c</sub></b>	MHz	-	2492	-
<b>Insertion Loss</b> (2488~2496 MHz) <b>IL</b>	dB	-	5.8	8
<b>Amplitude Ripple</b> (2488~2496 MHz)	dB	-	0.4	2.0
<b>3 dB Bandwidth</b> <b>BW<sub>-3dB</sub></b>	MHz	8	23	-
<b>Group Delay Ripple</b> (2488~2496 MHz)	ns	-	12	25
<b>VSWR</b> (2488~2496 MHz)	-	-	1.5	2.0
<b>Attenuation</b> (Reference level from 0 dB)				
10 ~ 1000 MHz	dB	45	62	-
1000 ~ 2000 MHz	dB	25	62	-
2000 ~ 2470 MHz	dB	15	27	-
2515 ~ 2520 MHz	dB	15	38	-
2520 ~ 3000 MHz	dB	20	50	-
3000 ~ 6000 MHz	dB	15	32	-

### C. MEASUREMENT CIRCUIT:

HP Network analyzer




### D. Frequency Characteristics:




Reflection Functions:


S11



S22



**E. OUTLINE DRAWING:**



**B: Input**

**E: Output**

**A, C, D, F: Ground**

**Unit: mm**


$\triangle$  : Year Code (2011->1, 2012->2, ..., 2019->9, 2020->0)

$\square$  : Date Code

**Date Code Table:**

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z



**F. PCB Footprint:**




## G. PACKING:

### 1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)




### 2. TAPE DIMENSION



### H. Recommended Reflow Profile:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C+0/-5°C peak (20~40sec).
4. Time: 2 times.



单击下面可查看定价，库存，交付和生命周期等信息

[>>TAI-SAW\(台湾嘉硕\)](#)