


# Wire Wound Power Common Mode Filter WCM5555FASV-SERIES-LM

## 1. Features

1. High reliability -Reliability tests comply with AEC-Q200
2. Operating temperature-40~+125°C (Including self - temperature rise)




## 2. Dimension



Series	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)	G(mm)
WCM5555	5.5±0.5	5.5±0.5	3.5 max.	3.3 typ.	1.2±0.5	1.9±0.5	1.1±0.5

Unit:mm

## 3. Part Numbering









- A: Series  
 B: Dimension  
 C: Material                      Ferrite Core  
 D: Process                        Assembled  
 E: Type                            S=Shielded , N=Unshielded  
 F: Category Code                V=Vehicle  
 G: Impedance                    701=700Ω  
 H: Laser Marking

## 4. Specification


TAI-TECH Part Number	Impedance (Ω)		Test Frequency (MHz)	DC Resistance (mΩ) max. (1 line)	Rated Current (A) max.	Rated Volt. (Vdc) max.	Insulation Resistance (MΩ) min.
	min.	typ.					
WCM5555FASV-101-LM	100	140	100	6.0	8.5	80	10
WCM5555FASV-301-LM	150	300	100	7.5	4.8	80	10
WCM5555FASV-501-LM	300	500	100	10.5	4.5	80	10
WCM5555FASV-701-LM	500	700	100	13.0	3.8	80	10
WCM5555FASV-102-LM	750	1000	100	20.0	3.0	80	10
WCM5555FASV-142-LM	1000	1400	100	38.0	2.8	80	10

Note:

- Measurement board data
- Material : FR4
- Board dimensions : 100 X 50 X 1.6t mm
- Pattern dimensions: 45 X 30 mm (Double side board)
- Pattern thickness : 50 μm



### 5. Schematic Diagram



单击下面可查看定价，库存，交付和生命周期等信息

[>>TAI-TECH\(台庆\)](#)