

Wire Wound Type Common Mode Filter



WCM2012F2SV-SERIES

1. Features

1. High common mode impedance at high frequency cause excellent noise suppression performance.
2. WCM2012F2SV series realizes small size and low profile. 2.0x1.2x1.2 mm.
3. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
4. High reliability -Reliability tests comply with AEC-Q200
5. Operating temperature-55~+125°C (Including self - temperature rise)



2. Dimension



Series	A(mm)	B(mm)	C(mm)	D1(mm)	D2(mm)	E(mm)
2012F2SV	2.0±0.2	1.2±0.2	1.2±0.2	0.50±0.1	0.51±0.1	0.15±0.1

3. Part Numbering









WCM	2012	F	2	S	V	-	900	T	04
A	B	C	D	E	F		G	H	I


- A: Series
 B: Dimension
 C: Material Ferrite Core
 D: Number of Lines 2=2 lines
 E: Type S=Shielded , N=Unshielded
 F: Category Code V=Vehicle
 G: Impedance 900=90Ω
 H: Packaging T=Taping and Reel
 I: Rated Current 04=400mA

4. Specification


TAI-TECH Part Number	Common mode Impedance (Ω)	Test Frequency (MHz)	DC Resistance (Ω) max.	Rated Current (mA)max.	Rated Volt. (Vdc)max.	Withstand Volt. (Vdc) max.	IR (Ω) min.
WCM2012F2SV-670T04	67±25%	100	0.25	400	50	125	10M
WCM2012F2SV-900T04	90±25%	100	0.30	400	50	125	10M
WCM2012F2SV-121T04	120±25%	100	0.30	400	50	125	10M
WCM2012F2SV-161T03	160±25%	100	0.35	350	50	125	10M
WCM2012F2SV-181T03	180±25%	100	0.35	350	50	125	10M
WCM2012F2SV-201T03	200±25%	100	0.40	300	50	125	10M
WCM2012F2SV-221T03	220±25%	100	0.40	300	50	125	10M
WCM2012F2SV-261T03	260±25%	100	0.40	300	50	125	10M
WCM2012F2SV-361T03	360±25%	100	0.50	300	50	125	10M

Typical Impedance v.s. Frequency Curve





5. Schematic Diagram



单击下面可查看定价，库存，交付和生命周期等信息

[>>TAI-TECH\(台庆\)](#)