

Single phase 250Vac 6 to 30A EMC Filters

https://product.tdk.com/en/products/emc/emc/power-line/tec_data/tdk_nf_rskn.html

<https://www.emea.lambda.tdk.com/uk/products/r-series>



Industrial



Test



LED



COMM



Broadcast

The RSKN single-phase, wide band, two stage high attenuation EMC filters are enclosed in a low profile metal case and are rated for 250Vac. Four current ratings of 6 to 30A enables the optimum attenuation to match the current rating. The RSKN series uses a nano crystal core for enhanced performance. The connection terminals are integrated into the case and a terminal cover provided for safety protection to avoid lost hardware. The RSKN series is UL certified for a short circuit current rating of 5,000A with the appropriate breaker.

Features

- Wide Band, High Attenuation
- 6 to 30A Current Ratings
- Integrated Terminal Block
- Safety Certified

Benefits

- Improved Performance
- Optimizes the Attenuation for the Current Rating
- No Lost Hardware
- Global Use

Model Selector

Model	Rated Current (A)	SCCR (kA)	HV Pulse Protection	Maximum DC Resistance (mΩ)	Attenuation frequency range (MHz)	
					Common mode at 30dB	Differential mode at 25dB
RSKN-2006	6	5	Y	300	0.2 to 30	0.4 to 30
RSKN-2010	10	5	Y	100	0.2 to 30	0.5 to 30
RSKN-2020	20	5	Y	20	0.3 to 30	0.4 to 30
RSKN-2030	30	5	Y	10	0.4 to 30	0.4 to 30

RSKN	-	2	06
Series Name		Rated Voltage 2 = 250Vac	Rated Current 006 = 6A 030 = 30A

Related Single Phase Filter Products

Type	Options								
	Current Raiting (A)	Series	Low Leakage	Faston on terminals	Wire leads	DIN Rail Mount	Fused	Discharge Resistor	Metal case
Board mount line filter, HV Pulse	0.5 - 6	RSAG							
Board mount line filter	0.5 - 6	RSEG							
General purpose with faston terminals	6	RSEC							
General purpose	0.5 - 6	RSEL	Y	Y	Y				Y
HV pulse protection	0.5 - 6	RSAL	Y	Y	Y				
Power Entry Module with line filter	3, 6, 10	RPE	Y				Y	Y	
Power Entry Module with line filter, HV Pulse	3, 6, 10	RPA	Y					Y	
Multipurpose	3 - 300	RSEN	Y (Up to 30A)			Y (Up to 30A)			
Multipurpose with HV pulse protection	3 - 60	RSAN	Y (Up to 30A)			Y (Up to 30A)			
High attenuation	3 - 300	RSHN	Y (Up to 30A)			Y (Up to 30A)			
High attenuation with pulse protection	3 - 300	RSMN	Y (Up to 30A)			Y (Up to 30A)			
Wide band, high attenuation	6 - 30	RSKN							

* Separate mounting bracket

[Click here for TDK-Lambda three phase filters](#)


Specification					
Model		RSKN-2006	RSKN-2010	RSKN-2020	RSKN-2030
Input					
Rated Voltage	Vac/Vdc	250 (Safety certified for AC input only)			
Input Frequency	Hz	47 - 63			
Leakage Current	mA	<1 at 250Vac, 60Hz			
Safety Certifications and Markings	-	UL1283, CSA C22.2 No.8 (cUL), EN60939-1 / -2 (SEMKO), conforms to RoHS Directive			
Environmental					
Operating Temperature	°C	-25 to +85. See derating curves below			
Storage Temperature	°C	-30 to +85			
Humidity (non condensing)	%RH	Operating: 30 - 90, storage: 10 - 95			
Cooling	-	Convection			
Withstand Voltage	Vac	2,500 input to earth			
Isolation Resistance (For 1 minute)	MΩ	>100 at 500Vdc			
Vibration	-	10-55Hz Amplitude 1.5mm, Sweep for 1 min. X, Y and Z directions for 2 hours each			
Other					
Weight (Typ)	g	220	310	530	660
Size (LxWxH)	mm	107 x 47 x 26	117 x 47 x 30	151 x 52 x 35	151 x 67 x 35
Size (LxWxH)	Inches	4.21 x 1.85 x 1.02	4.61 x 1.85 x 1.18	5.94 x 2.05 x 1.38	5.94 x 2.64 x 1.38
Connectors	-	M4 Screw terminals			
MIL-HDBK-217F NOTICE2	Hours	RSKN-2006: 5,137,690, RSKN-2030 : 4,641,664			
Warranty	Years	5			

Notes


See website for detailed specifications, test methods and installation manual [RSKN technical files](#)

Mechanical Specification


Derating Curve RSKN-2006/ -2010



Derating Curve RSKN-2020/ -2030



Schematic



[illegible]

Part No.	A	B	C	D
RSKN-2006	107	75	90	26
RSKN-2010	117	85	100	30

Technical drawing of the H1000-01 module, showing dimensions in mm.

Front View:


- Overall width: 132 ± 0.5
- Overall height: 44 ± 0.5
- Mounting holes: 2 - $\phi 4.8$ (MOUNTING HOLES)
- Terminal spacing: 17, 12, 10
- Terminal type: 6-M4
- Label area: 1, 2, 3, 4, FG, LABEL

Side View:

- Overall height: 35 ± 1
- Mounting flange width: 18MAX
- Label area width: 115 $\pm$ 1
- Overall width: 151MAX


Rear View:

- Overall height: 52 ± 1
- Mounting flange width: 18MAX
- Label area width: 115 $\pm$ 1
- Overall width: 151MAX


RSKN-2030 Outline Drawing


RSKN Attenuation vs. Frequency


RSKN-2006




RSKN-2010



RSKN-2020




RSKN-2030




RSKN Pulse Attenuation Characteristics


RSKN-2006




RSKN-2010



RSKN-2020



RSKN-2030



**TDK-Lambda France SAS**

Tel: +33 1 60 12 71 65
 ttf.fr-powersolutions@tdk.com
 www.emea.lambda.tdk.com/fr

**Italy Sales Office**

Tel: +39 02 61 29 38 63
 ttf.it-powersolutions@tdk.com
 www.emea.lambda.tdk.com/it

**Netherlands**

ttf.nl-powersolutions@tdk.com
 www.emea.lambda.tdk.com/nl

**TDK-Lambda Germany GmbH**

Tel: +49 7841 666 0
 tlq.powersolutions@tdk.com
 www.emea.lambda.tdk.com/de

**Austria Sales Office**

Tel: +43 2256 655 84
 tlq.at-powersolutions@tdk.com
 www.emea.lambda.tdk.com/at

**Switzerland Sales Office**

Tel: +41 44 850 53 53
 tlq.ch-powersolutions@tdk.com
 www.emea.lambda.tdk.com/ch

**Nordic Sales Office**

Tel: +45 8853 8086
 tlq.dk-powersolutions@tdk.com
 www.emea.lambda.tdk.com/dk

**TDK-Lambda UK Ltd.**

Tel: +44 (0) 12 71 85 66 66
 tlu.powersolutions@tdk.com
 www.emea.lambda.tdk.com/uk

**TDK-Lambda Ltd.**

Tel: +9 723 902 4333
 tli.powersolutions@tdk.com
 www.emea.lambda.tdk.com/il-en

**TDK-Lambda Americas**

Tel: +1 800-LAMBDA-4 or 1-800-526-2324
 tla.powersolutions@tdk.com
 www.us.lambda.tdk.com

**TDK Electronics do Brasil Ltda**

Tel: +55 11 3289-9599
 sales.br@tdk-electronics.tdk.com
 www.tdk-electronics.tdk.com/en

**TDK-Lambda Corporation**

Tel: +81-3-6778-1113
 www.jp.lambda.tdk.com

**TDK-Lambda (China) Electronics Co. Ltd.**

Tel: +86 21 6485-0777
 tlc.powersolutions@tdk.com
 www.lambda.tdk.com.cn

**TDK-Lambda Singapore Pte Ltd.**

Tel: +65 6251 7211
 tfs.marketing@tdk.com
 www.sg.lambda.tdk.com

**TDK India Private Limited, Power Supply Division**

Tel: +91 80 4039-0660
 mathew.philip@tdk.com
 www.sg.lambda.tdk.com



单击下面可查看定价，库存，交付和生命周期等信息

[>>TDK-Lambda](#)