
.960 .960 .960 .930 ±.008



.070 DIA.TYP.

-202 NON-ACCUM.

RECOMMENDED LAYOUT FOR

1. MATES WITH HOUSING 480277.

125 THICK P.C. BOARD

2. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-3

Linguished copy not to be reproduced nor published without written permission of AMP Incorporated

08SOLETE -2, 1-1,1-7,2-1, Kul RS 4-21G 2-13-1,3-7, 4-1,4-1,5-1,5-2,1-1,

F, RESTORED BKO ZS 4/3/65

F REV. PER M-7376 SS P 7-3085

E RCVISCO M-4/6/ MF NH 37-77


O ECN M-387/ SV NH 2-76

C ECN M-3852 SV NH 2-76

A ECN M-3152 SV NH 2-3/2

PER ECN M-2996 ST 67 (4-17)

REVISION RECORD ON CHE DATE



9. Sim.

E. Creamer

EMAHOUAUNO 6/11/13

6-11-73

3. DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

		-	
			-
	·		
·			
		1	
•	-		
		 	
		 	· · · · · · · · · · · · · · · · · · ·
		 	
-			
		 	•
		 	
· · · · · · · · · · · · · · · · · · ·			• • • • • • • • • • • • • • • • • • • •
			-
· · · · · · · · · · · · · · · · · · ·			
		<u> </u>	
`	-		
	:		
350577-1	NYLON - NATUE AL	PHOS BRE - PRE	TIN
ASSEMBLY NO	HSG. MATL É CCLOR	PIN MATL & F	INISH
O 19 75 THE HICORPORATED, ALL RIGHTS RESERVER.		CUSTOMER COMA	

SEE TABLE

RC. BOARD SOCKET HEA

G1 REVISED PER ECR-21-117185

Marin Marin

. Downloaded From Oneyac.com

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)