

4

3

2

1

© 2020 TE Connectivity. All Rights Reserved.

PROJECT	PRJ-14-000004825
PART NO.	X-2312501-X
DESCRIPTION	M12 A-CODED F-5 CABLE GLAND CONNECTOR FEMALE
CUSTOMER	GENERAL MARKET

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
B		REVISED PER ECR-20-010425	04AUG2020	GK	SE

7	(1)	COLOR RING (OPTIONAL)	THERMOPLASTIC
6	1	CABLE GLAND	Cu-ALLOY
5	1	DISC	Cu-ALLOY
4	1	DISC HEAD	Cu-ALLOY
3	1	CONTACT HOLDER	PA (THERMOPLAST)
2	-	ORDERED SEPARATELY	Cu-ALLOY GOLD-PLATED
1	1	FRONT HOUSING	Cu-ALLOY NICKEL-PLATED
SL. NO.	QTY	DESCRIPTION	MATERIAL

M12 A-CODED F-5 CABLE GLAND FEMALE CONNECTOR

SL. NO.	TE PART NO.	DESCRIPTION	No. of CONTACTS	OUTSIDE CABLE DIA
1	1-2312501-1	M12 A-CODED F-5 CABLE GLAND CONNECTOR FEMALE 4-6.5 mm	5	4-6.5 mm
2	1-2312501-2	M12 A-CODED F-5 CABLE GLAND CONNECTOR FEMALE 5.5-9 mm	5	5.5-9 mm

SHIELD DISC CHART		
PART NAME	CENTER HOLE SHIELD DISC	CABLE DIAMETER W/O OUTER SHEATH
SHIELD DISC 1	4 mm	3.9 mm MAX.
SHIELD DISC 2	5 mm	4.9 mm MAX.
SHIELD DISC 3	6 mm	5.9 mm MAX.
SHIELD DISC 4	7 mm	6.9 mm MAX.

CONTACTS TABLE					
M12 CODING	PIN/SOCKET	PICTURE	WIRE SIZE	TE P/N	DESCRIPTION
A5 CODING	REC		AWG20/22	1-2314103-1	M12 CRIMP CONTACT SOCKET 1mm Au 0.8μ
			AWG22/24	1-2314103-2	M12 CRIMP CONTACT SOCKET 1mm Au 0.8μ

NOTES:

PLEASE NOTE: CONTACTS NEED TO BE ORDERED SEPARATELY DEPENDING ON THE AWG SIZE.

- ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY.
- PACKAGING: 1 PIECE IN A BAG.
- THE CONNECTOR IS AS PER IEC 61076-2-101.
- TEMPERATURE RANGE: -40°C TO 85°C.
- VIBRATION & SHOCK TEST CONDUCTED AS PER IEC 61373:1999.
- FIRE PERFORMANCE CONDUCTED AS PER EN45545-2, NFF16-101 AND NFF16-102.
- THE THREAD OF THE MATING INTERFACE WITH THE COUNTERPART IS M12x1 ACCORDING TO IEC61076-2-101.
- SUPPLIER RECOMMENDED CRIMP INSERT: SHOULD BE VALIDATED ON CABLE USED.
- CONTACTS & SHIELD DISCS SHALL BE SUPPLIED BY THE SUPPLIER.
- SHIELD DISC 1 - 4 ARE SUPPLIED IN THE BOX.

48.5⁰_{-2.9}

ø15.5

SW14

SW13

SW12 max.1Nm

M12x1

SHOWN 1-2312501-1

50.9^{+0.1}₋₁

ø18.9

SW17

SW13

SW12 max.1Nm

M12x1

SHOWN 1-2312501-2

ISO VIEW

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN GOPALAKRISHNA HV 04AUG2020			NAME	
DIMENSIONS: mm		CHK S. EGBERT 04AUG2020			M12 A-CODED F-5 CABLE GLAND CONNECTOR FEMALE	
TOLERANCES UNLESS OTHERWISE SPECIFIED: DIN ISO 2768 m		APVD S. EGBERT 04AUG2020	PRODUCT SPEC		SIZE	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APPLICATION SPEC	108-156001		CAGE CODE	
MATERIAL		FINISH	114-156002		DRAWING NO	
			CUSTOMER DRAWING		SCALE	
			A2 00779		SHEET	
			G=2312501		1 of 1	
					REV	
					B	

1471-9 (1/15)

Downloaded From Onevac.com

2312501

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)