



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01_0	RELEASED	3/7/97	S. Morby

NOTES:
1. CAPTURED CENTER CONTACT

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH								
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating <u>-65°C to +125°C</u>	BRASS, PER ASTM-B-16 HALF HARD OR CZ121 PER BS2874	TFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197 ALLOY C17300, CONDITION H	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	WHITE BRONZE PLATE								
Frequency Range (GHz) <u>DC to 6</u>	Recommended Mating Torque <u>3-5 in-lbs (0.34-0.57 Nm)</u>	Vibration MIL-STD-202, Method 204, Condition D				FRAC. DEC. ANGLES	<table border="1"> <tr> <td>SIZE</td> <td>CODE IDENT NO.</td> <td>2252-1901-36</td> <td>REV</td> </tr> <tr> <td>B</td> <td>26805</td> <td></td> <td>01_0</td> </tr> </table>	SIZE	CODE IDENT NO.	2252-1901-36	REV	B	26805		01_0	N/A
SIZE	CODE IDENT NO.	2252-1901-36	REV													
B	26805		01_0													
Volt Rating (VRMS MAX) <u>Sea Level 335</u>	Mating Characteristics: Insertion (MAX Lbs) <u>3.0 (1.36 Kg)</u>	Shock MIL-STD-202, Method 213, Condition I				±1/64 ±.005 ± 1°	GOLD PLATE									
VSWR <u>1.40:1</u>	Withdrawal (MIN Oz) <u>1.0 (28.35 g)</u>	Thermal Shock MIL-STD-202, Method 107, Condition A				These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.										
Insertion Loss (dB MAX) <u>.07√f(GHz)</u>	Force to Engage and Disengage (in-Lbs MAX) <u>2.0 (0.23 Nm)</u>	Moisture Resistance MIL-STD-202, Method 106, except step 7b is omitted. No measurement at high humidity. Insulation resistance shall be at least 200 Megohms within 5 minutes after removal from humidity.				USE ASS'Y PROCEDURE										
RF Leakage (dB MIN) <u>-90 @ 2 to 3 GHz</u>	Center Contact Captivation: Axial (Lbs) <u>6.0 (2.7 Kg) MIN FROM INTERFACE</u>					NO. AP. <u>N/A</u>										
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Axial (Lbs) <u>4.0 (1.8 Kg) MIN FROM FLANGE</u>															
Dielectric Withstanding Voltage (VRMS MIN) <u>Sea Level 1000</u>	Radial (in-Oz) <u>4.0 (0.028 Nm)</u>															
Contact Resistance (Milliohms MAX): Center Contact <u>3.0</u>	Weight (Grams) <u>TBD</u>															
Outer Contact <u>2.0</u>																
Cable to Housing <u>N/A</u>																
RF High Potential <u>Sea Level (VRMS MIN @ 5 MHz) 670</u>																
I.R.(Megohms MIN) <u>5,000</u>																
			.XXX = in XX.X = mm (REF)			TITLE: SMA.com 4 HOLE FLANGE MOUNT JACK RECEPTACLE, STRAIGHT TERMINAL										
			SCALE: 4:1			SHEET 1 OF 1										

CUSTOMER DRAWING

AMP PART # 1086493-1
SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)