10-10-06

В



100 OHM, AWG 22, 19 STRANDS OF AWG 34, Date: UNSHIELDED, UNJACKETED, TWO CONDUCTOR CABLE Revision:

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.


CONSTRUCTION DETAILS

ELECTRICAL CHARACTERISTICS

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.

CHARACTERISTIC IMPEDANCE 100 ± 10 ohms, Method C at 1 MHz

CAPACITANCE 16.0 pF/ft. (nominal)



ADDITIONAL REQUIREMENTS

COMPONENT WIRE PRIOR TO CABLING (Test Procedures per AS22759)

CROSSLINK PROOF $300 \pm 3^{\circ}$ C for 1 hour,

> .500 inch mandrel, .250 lb., 2.5 kV dielectric test

LOW TEMPERATURE -65 ± 2°C for 4 hours, COLD BEND .750 inch mandrel, 1.00 lb.,

2.5 kV dielectric test

SHRINKAGE 200 ± 3°C for 1 hour, .125 inch

(maximum) in 12 inches

INSULATION RESISTANCE 5000 megohms for 1000 ft. (minimum) INSULATION (DIELECTRIC)

TENSILE STRENGTH

5000 lbf/in2 (minimum) **ELONGATION** 50% (minimum)

INSULATION FLAWS

SPARK TEST 3.0 kV (rms) IMPULSE TEST 8.0 kV (peak) INSULATION WALL THICKNESS $.007 \pm .001$ inch

FINISHED CABLE

INSULATION FLAWS

3.0 kV (rms) SPARK TEST IMPULSE TEST 8.0 kV (peak)

Other codes and suffixes may be added to the part number, as

WEIGHT

5.7 lbs/1000 ft. (nominal)

necessary, to capture any additional requirements imposed by the purchase order.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



087



501 Oakside Avenue Redwood City, California 94063-3800 1-800-227-8816 Fax: 1-650-361-6297 THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

© 2006 Tyco Electronics Corporation. All rights reserved.

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)