

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MATED WITH
PASSEND ZU
HA 16

COPYRIGHT - By -

ALL RIGHTS RESERVED.

PROJEKT NR.:

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D6	ECR-17-009069	09FEB2018	SG	MKO

SCREW TERMINATION 4 M3x10.5

CRIMP TERMINATION 5 M3x10.5

SPRING CLAMP TERMINATION 6 M3x10.5

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. $\phi 3,2$ MMSUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264Strip length: Screw connection 10mm
Spring clamp connection 10mm Crimp connection 7.5mmSTANDARDS:
DIN EN 61984; DIN EN 60664-1PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTEDSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECESSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECESSPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECESSPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

SEE TE CONNECTIVITY QUALITYMANAGEMENT PROCEDURE NO. 1.12

Panel cut-out for contact insert

when used without housing

Assembling instruction

DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

1-3	1-2	1-0	0-4	0-7	0-6	0-5	2-9	1-9	7-9	7-8	1-8	2-8	1-7	7-2	7-1	2-3	1-1	DESCRIPTION / BENENNUNG	MATERIAL	COLOR / FARBE	ITEM NO. POS.	REMARKS / BEMERKUNGEN
								1										Pin insert screw	PBT	light beige	8	with stainless steel-fixing screw
								1										Pin insert screw	PBT	light beige	7	with stainless steel-fixing screw
								1										Pin insert screw	PBT	light beige	6	with AU contact
									1	1								Cover	PBT	light beige	5	
											1	1						Cover	PBT	light beige	4	
													1					Cover	PBT	light beige	3	
														1				pin insert spring clamp	PBT	light beige	2	
															1			pin insert crimp/screw	PBT	light beige	1	

HA-16.Sti.S.B1-16.WIE	HA-16.Sti.S.B1-16.AIS	HA-16.Sti.S.B17-32.KM	HA-16.Sti.S.B1-16.KM	HA-16.Sti.S.VA.B1-16	HA-16.Sti.S.VA.B17-32	HA-16.Sti.S.AU.B1-16	HA-16.Sti.S.C.B.49-64	HA-16.Sti.S.B.49-64	HA-16.Sti.S.C.B.49-64	HA-16.Sti.S.C.B.33-48	HA-16.Sti.S.B.33-48	HA-16.Sti.S.C.B.33-48	HA-16.Sti.S.B.17-32	HA-16.Sti.S.C.B.17-32	HA-16.Sti.S.C.B.1-16	HA-16.Sti.S.B.1-16	ORDERING TEXT / BESTELLTEXT	THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	09.02.2000	Schneider	
																		CHK	09.02.2000	APVD	Schweiger		
DIMENSIONS: mm																		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		Male insert	
																		0 PLC		+		-	
																		1 PLC		+		-	
																		2 PLC		+		-	
																		3 PLC		+		-	
																		4 PLC		+		-	
																		ANGLES		+		-	
																		FINISH		+		-	
MATERIAL																		PRODUCT SPEC		108-74007		APPLICATION SPEC	
MATERIAL																		WEIGHT		114-77009		SCALE	
MATERIAL																		CUSTOMER DRAWING		A2		CAGE CODE	
MATERIAL																		WEIGHT		00779		DRAWING NO	
MATERIAL																		WEIGHT		00779		RESTRICTED TO	
MATERIAL																		WEIGHT		00779		SCALE	
MATERIAL																		WEIGHT		00779		SHEET	
MATERIAL																		WEIGHT		00779		1 OF 1	
MATERIAL																		WEIGHT		00779		REV	
MATERIAL																		WEIGHT		00779		D6	

1471-9 (1/15)

Downloaded From Oneyac.com

1103416

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)