



| REVISIONS | | | |
|-----------|-------------|--------|-------------------|
| REV | DESCRIPTION | DATE | APPROVED |
| 010 | RELEASED | 2/8/93 | <i>D. Comello</i> |

| ELECTRICAL | MECHANICAL | ENVIRONMENTAL | HOUSING | MATERIAL | FINISH |
|---|--|---|---|---|--|
| Nominal Impedance (Ohms) <u>50</u> | Interface Dimensions MIL-STD-348A, Fig. <u>310.2</u> | Temperature Rating <u>-65°C to +125°C</u> | DIELECTRIC | STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303 | PASSIVATE PER QQ-P-3580 |
| Frequency Range (GHz) DC to <u>18</u> | Recommended Mating Torque <u>N/A</u> | Vibration MIL-STD-202, Method 204, Condition D. | CENTER CONTACT | PTFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| Volt Rating (VRMS MAX) @ Sea Level <u>335</u> | Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u> | Shock MIL-STD-202, Method 213, Condition I. | | BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550 |
| VSWR <u>N/A</u> | Withdrawal (MIN Oz) <u>1.0</u> | Thermal Shock MIL-STD-202, Method 107, Condition A. | | | |
| Insertion Loss (dB MAX) <u>N/A</u> | Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u> | Except High Temp shall be +115°C | | | |
| RF Leakage (dB MIN) <u>[-60-f(GHz)]</u> | Center Contact Captivation: Axial (Lbs) <u>6.0</u> | Moisture Resistance MIL-STD-202, Method 106 | COMPONENT | | |
| Corona, 70,000 Ft (VRMS MIN) <u>250</u> | Radial (In-Oz) <u>4.0</u> | Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray | | | |
| Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u> | Cable Retention: Axial Force (Lbs) <u>N/A</u> | | | | |
| Contact Resistance (Milliohms MAX): Center Contact <u>2.0</u> | Torque (In-Oz) <u>N/A</u> | | | | |
| Outer Contact <u>2.0</u> | Weight (Grams) <u>1.7</u> | | | | |
| Cable to Housing <u>N/A</u> | | | | | |
| RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u> | | | | | |
| I.R.(Megohms MIN) <u>10,000</u> | | | | | |
| | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON | DRAWN BY <i>A. Davis</i> DATE <u>1/12/93</u> CHECKED BY APP'D BY <i>D. Comello</i> <u>2/8/93</u> AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 | |
| | | | FRAC. DEC. ANGLES <u>± 1/64 ±.005 ± °</u> | TITLE OSM 2 HOLE FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL USE ASS'Y PROCEDURE NO. AP. <u>N/A</u> | |
| | | | These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission. | SIZE <u>B</u> CODE IDENT NO. <u>26805</u> 2052-1300-02 REV <u>010</u> SCALE <u>5 : 1</u> SHEET 1 OF 1 | |

CUSTOMER DRAWING AMP PART # 1052534-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)