



7. CABLE ACCOMMODATION DIMS:
 JACKET DIA. ----- .088 MAX
 DIELECTRIC DIA. ----- .032-.042
 INNER CONDUCTOR DIA. --- .009-.019
 FOR ENVIRONMENTAL SEAL USE EXTRUDED JACKET
6. FOR ELECTRICAL, MECHANICAL, & ENVIRONMENTAL SPECS. SEE MALCO CATALOG.
5. .016 DIA. WIRE HOLE 3 PLACES
4. GOLD PLATE PER MIL-G-45204 TYPE II, GRADE-C, CLASS I.
3. DELETED
2. SEE RF-ASMB-8 ASSY INSTRUCTIONS. SPECIAL TOOL REQ'D: CONTACT CRIMP: 010-0134-0000 & LOCATOR 001-0104-0000. ALTERNATE TOOL 010-0065-0000 (NO LOCATOR REQUIRED.) HOUSING CRIMP: 010-0081-0000.
1. THIS CONNECTOR MATES WITH ALL 50 Ω GOLDEN CRIMP, CRIMP SILVER & ALL S-50 JACKS & RECEPTACLES AS LISTED IN MALCO CATALOG.

NOTES: UNLESS OTHERWISE SPECIFIED

| | | | | | | | | |
|---|------------|---|---|---|---------------|--|----------------------------|------|
| | | | | | | DELETED | | (11) |
| | 1 | 1 | 1 | 1 | 003-0815-0001 | SEALING SLEEVE | SILICONE RUBBER MIL-R-5847 | (10) |
| 4 | 1 | 1 | 1 | 1 | 003-0813-0002 | MIDDLE SLEEVE | LEADED COPPER | (9) |
| 4 | 1 | 1 | 1 | 1 | 003-0814-0002 | INNER SLEEVE | BRASS, QQ-B-626 | (8) |
| | 1 | 1 | 1 | 1 | 003-0811-0001 | CABLE INSULATOR | TEFLON PER L-P-403 | (7) |
| | | | | | | DELETED | | (6) |
| 4 | 1 | 1 | 1 | 1 | 003-0867-0002 | PIN CONTACT | COPPER ALLOY | (5) |
| 5 | 4 | | | | 003-1298-0004 | HOUSING SUB-ASSY NUT-1/4" HEX W/WIRE HOLES | BRASS PER QQ-B-626 | (4) |
| 4 | | 1 | | | 003-1298-0003 | HOUSING SUB-ASSY NUT-1/4" HEX | BRASS PER QQ-B-626 | (3) |
| 4 | | | 1 | | 003-1298-0002 | HOUSING SUB-ASSY NUT-1/4" KNURL | BRASS PER QQ-B-626 | (2) |
| 4 | | | | 1 | 003-1298-0001 | HOUSING SUB-ASSY NUT-1/4" PARTIAL HEX | BRASS PER QQ-B-626 | (1) |
| | 4 | 3 | 2 | 1 | COMPONENT | NOMENCLATURE | MAT'L & SPEC. | ITEM |
| | DASH NO. * | | | | No. | | | |

| | | | | | | | | | |
|-------------------|--|--|--|----------------------|--|--|--|--|--|
| F 23178 | | REVISED & REDRAWN 3-78 | | 3/14/78 | | STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED | | MALCO A MICRODOT COMPANY, INC. 220 PASADENA AVE., SO. PASADENA, CA | |
| G 24191 | | NOTE 2 WAS: ASSY TOOL REQ'D 010-0065-0000 OR 010-0134-0000 FOR CONTACT, 010-0081-0000 FOR HOUSING. NOTE 3 WAS: CENTER CONDUCTOR 5-1-75 Zhuan | | 5/14/79 | | DEC. = FRAC. = ANGLES = ECCENTRICITY MAX. T.I.R. = HOLE DIA. = SURFACE ROUGHNESS | | SURFACE TREATMENT NOTED | |
| ASSEMBLY NO REQ'D | | | | | | MICRO INCHES INCREASING TO MIL-S-7742 COMMERCIAL TOLERANCES APPLY TO STOCK DIMENSIONS | | MATERIAL NOTED | |
| NEXT ASSEMBLIES | | LET ECO | | REVISION DESCRIPTION | | DATE | | APP | |
| | | | | | | | | APP | |
| | | | | | | | | CHECKED BY C.E.H. | |
| | | | | | | | | DRAWN BY D.D. | |
| | | | | | | | | SCALE WT DATE | |
| | | | | | | | | 3-3-78 | |
| | | | | | | | | DRAWING NUMBER | |
| | | | | | | | | CDM 132-0113-000* | |
| | | | | | | | | G | |

PLUG ASSEMBLY
 ENVIRONMENTAL
 GOLDEN CRIMP 50 Ω

PROD CODE 941
 CODE CDM 132-0113-000*
 DATE 3-3-78

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)