



SUGGESTED PC BOARD LAYOUT  
 COMPONENT SIDE  
 SEE APPLICATION SPECIFICATION

LOC	DIST	REV	DESCRIPTION	DATE	BY	APP'D
AA	22	P	REV PER ECR-08-032447	23FEB2009	DZ	SY

△ MATERIAL: HOUSING-PCT POLYESTER, BLACK IR COMPATIBLE, UL 94V-0.  
 TERMINALS-.33 [.013] THICK PHOS BRONZE PLATED WITH 1.27 $\mu$ m [.000050] THICK HARD GOLD IN LOCALIZED AREA AND 3.81 $\mu$ m [.000150] THICK MATTE TIN IN SOLDER AREA OVER 1.27 $\mu$ m .000050 THICK NICKEL UNDERPLATE.  
 SHIELD-0.254 [.010] THICK COPPER ALLOY PLATED WITH 1.27 $\mu$ m [.000050] MINIMUM NICKEL AND 2.03  $\mu$ m [.000080] MINIMUM HOT TIN DIP ON PCB GROUND TABS.  
 △ JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS, PART 68 SUBPART F.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	OTHERWISE SPECIFIED:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm		0 Plc ± -
		1 Plc ± -
		2 Plc ± 0.254[.01]
		3 Plc ± 0.127[.005]
		4 Plc ± -
		ANGLES ± -

MATERIAL SEE NOTE 1

FINISH SEE NOTE 1

DMN	23MAR2005	5558188-1
CHK	C. YATES/LAMMETER	PART NO.
APP'D	J. WESTMAN	
PRODUCED BY	S. ELICKINGER	
PRODUCT SPEC	108-1163-1	
APPLICATION SPEC	114-2048	
WEIGHT	-	

Customer Drawing

Tyco Electronics Corporation  
 Harrisburg, Pa 17105-3608

MODULAR JACK ASSEMBLY,  
 4 PORT, 8 POSITION,  
 RIGHT ANGLE, SHIELDED

SIZE A2  
 CAGE CODE 00779  
 DRAWING NO. 5558188

RESTRICTED TO

SCALE 2:1 SHEET 1 OF 1 REV C

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)