



- .035 DIA HOLE IS RECOMMENDED FOR .125 MAX THICK P.C. BOARD.
- CONNECTOR MATES WITH ANY AMP 78 POSN PLUG.
- POST TIPS WILL FALL WITHIN $\phi .020$ TRUE POSITION OF EACH OTHER.
- UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- FINISH: CADMIUM PER QQ-416.
- FINISH: ZINC PLATED PER ASTM-B-633 .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+).

REMARKS	- $\triangle 6$.375 MAX	.275±.025	5-211596-1
	NOT RELEASED FOR PRODUCTION $\triangle 5$.275 MAX	.375±.025	211596-2
	-	.375 MAX	.275±.025	211596-1
		DIM B	DIM A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	8-11-97	Tyco Electronics Corporation Harrisburg, PA 17105-3608
		C.C.THOMAS	11-24-97	
		CHK	H.WYNKOOP	Tyco Electronics
		APVD		
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	NAME		
	0 PLC ± -	PRODUCT SPEC		
	1 PLC ± -	APPLICATION SPEC		
	2 PLC ± -	SIZE		
	3 PLC ± .005	CAGE CODE		
	4 PLC ± -	DRAWING NO		
	ANGLES ± -	RESTRICTED TO		
MATERIAL SEE CALLOUTS	FINISH SEE CALLOUTS	WEIGHT	A1 00779	211596
CUSTOMER DRAWING		SCALE	4:1	SHEET 1 OF 1 REV J

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)