



- ⚠ INSERTS WILL WITHSTAND 6 IN. LBS. TORQUE AND 50 LBS. PULL OUT FORCE FROM MATING FACE SIDE.
- ⚠ MOLDED PARTS: FLAME RETARDANT 94V-2 RATED NYLON, COLOR: BLACK
CONTACTS: BRASS
INSERTS: BRASS
- ⚠ GOLD PLATED FOR LENGTH OF .150 MIN FROM MATING END, .000030 MIN GOLD IN MATED AREA, .000100 MIN TIN-LEAD ON OPPOSITE END, BOTH OVER .000050 MIN NICKEL.
-OR-
GOLD FLASH OVER PALLADIUM NICKEL FOR A LENGTH OF .150 MIN FROM MATING END, .000030 MIN PALLADIUM NICKEL IN MATED AREA, .000100 MIN TIN-LEAD ON OPPOSITE END, BOTH OVER .000050 MIN NICKEL.
- ⚠ GOLD PLATED FOR LENGTH OF .150 MIN FROM MATING END, GOLD FLASH IN MATED AREA, .000100 MIN TIN-LEAD ON OPPOSITE END, BOTH OVER .000050 MIN NICKEL.

SUPERSEDED BY 745001-2	-	-	-	745001-9
OBSOLETE	-	-	-	745001-8
OBSOLETE	TUBES	WITH INSERTS	⚠	745001-7
OBSOLETE	-	-	-	745001-6
OBSOLETE	-	-	-	745001-5
	TUBES	WITH .125 DIA HOLE	⚠	745001-3
	TUBES	WITH .125 DIA HOLE	⚠	745001-2
OBSOLETE	-	-	-	745001-1
PACKAGING	REMARKS	CONTACT FINISH	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: K.FOLTZ 09/21/93	Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK: R.STONE 9-22-93	Harrisburg, PA 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD: J.L. DOMINGOS 9-23-93	NAME: J.L. DOMINGOS	
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± -	4 PLC ± .005
ANGLES ± ± -		PRODUCT SPEC: 108-40025		
MATERIAL: ⚠		APPLICATION SPEC: -		
FINISH: CONTACTS: SEE TABLE		SIZE: A1	CAGE CODE: 00779	DRAWING NO: 745001
CUSTOMER DRAWING		SCALE: 4:1	SHEET: 1 OF 1	REV: M

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)