

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AG	00	G3	REVISED PER ECO-13-007818	09MAY2013	KH AS

1 MATERIAL:
 EYELET - COPPER (QQ-C-576)
 SPRING - BERYLLIUM COPPER (QQ-C-533)
 SEALANT - SILICONE RUBBER

2 TIN PLATE (MIL-T-10727)0.00381 [.000150] MIN THK.

3 TIN PLATE(MIL-T-10727)0.00254 [.000100] MIN THK.

4 GOLD PL(MIL-G-45204)0.00076 [.000030] MIN THK ON CONTACT AREA.

5 PACKAGED 50,000 PER REEL

6 TO INSURE 1/2 OZ MIN RETENTION DO NOT EXCEED 0.10 [.004] DIFFERENCE IN PIN DIA WHEN CHANGING TO A SMALLER DIA PIN

7 PRODUCT IS OVALIZED FOR RETENTION IN THE P.C. BOARD. THE RECOMMENDED HOLE DIAMETER IS $\phi 1.07$ [$\phi .042$] MINIMUM, +0.08 [.003] MAX. PRIOR TO SOLDERING.

8 TIN-LEAD PLATE 0.00381 [.000150] MIN THK.

9 PACKAGED 10,000 PER REEL

OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	GOLD 4	TIN 2	5	1-645947-7
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	GOLD 4	TIN 8	9	1-645947-6
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.30-\phi 0.46$ [$\phi .012-\phi .018$]	GOLD 4	TIN 2	9	1-645947-5
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.30-\phi 0.46$ [$\phi .012-\phi .018$]	TIN 3	TIN 2	9	1-645947-4
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	GOLD 4	TIN 2	9	1-645947-2
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	TIN 3	TIN 2		1-645947-1
OBSOLETE	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	GOLD 4	TIN 2	5	645947-2
SUPERSEDED BY 5645947-1	2.29-3.68 [.090-.145]	$\phi 0.38-\phi 0.53$ [$\phi .015-\phi .021$]	TIN 3	TIN 2	5	645947-1
	LENGTH	DIA	FINISH			PART NO
			SPRING	EYELET		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	12-20-82	M.BOWERS	
DIMENSIONS: mm [INCHES]		CHK	6-10-85	P.MUTZABAUGH	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	6-10-85	G.MILLER	
0 PLC	± -	PRODUCT SPEC		NAME	
1 PLC	± -	APPLICATION SPEC		MINIATURE SPRING SOCKET ASSY	
2 PLC	± -	114-26004		SERIES 1 SHORT	
3 PLC	± 0.20[.008]	WEIGHT -		WITH SEALANT	
4 PLC	± -	CUSTOMER DRAWING		RESTRICTED TO	
ANGLES	± -	SCALE NTS		SHEET 1 OF 1	
FINISH	SEE TABLE	SHEET 1 OF 1		REV G3	

1471-9 (3/11)

Downloaded From Onevac.com

645947

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)