

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	E6	REVISED	ECR-16-000439	31AUG07	TS	KB

Dimensions: (31), 22±0.5, 3.5, (0.5), <R3>, 2-φ2.3±0.15, -AMP, -A-

Dimensions: 16.7±0.5, 12.3±0.2, 3.75, 6, 8.5, 3.15, 0, 5, 12, 19, 0.9, 43±0.5, (36), 28.6±0.5, 25.3, +0.3, -0.2, -A-

注記:

-A- 面より2mmの範囲で測定のこと。
 △ 相手ハウジングと所定の機能を満たしてかん合できること。
 △ フードの反りは0.2以内。
 4 推奨取付けねじ: JIS B 1115 又は、1122 タッピンねじ
 なべ1種又は2種、呼び径3長さ6mm以下。
 (締め付けトルク: 0.4N・m 以下)
 5 適用製品規格 No.108-5093
 6 相手ハウジングとのかん合力は、29.4N以下
 但し、リセプタクルコンタクトは含まない。
 △ タブなしタイプ(表参照)回路番号下図参照のこと。

NOTES:

△ TO BE MEASURED WITHIN 2mm FROM -A-
 △ IN COUPLING WITH THE PLUG HOUSING MATING SATISFIES
 FUNCTION
 △ WARPAGE 0.2 MAX.
 4 RECOMMENDED MOUNTING SCREW; 3mmDIA, 6mmLENGTH<MAX.>
 PAN HEAD, CLASS 1 AND 2 TAPPING SCREW SPECIFIED IN JIS
 B1115, B1122 <TIGHTENING TORQUE 0.4N・m MAX.>
 5 SPEC. No. 108-5093
 6 IN COUPLING WITH THE PLUG HOUSING MATING FORCE
 29.4N MAX WITHOUT RECEPTACLE CONTACT
 △ NON TAB CONTACT'S TYPE <SEE TABLE>
 CIRCUIT NUMBER

7 6 5
4 3 2 1

プリント基板取付穴寸法図
 (MOUNTING DIMENSIONS FOR P.C.BOARD)

1. 板厚, 1.6±0.15
 (P.C.B. THICKNESS, 1.6±0.15)
 2. 公差, ±0.1
 (TOLERANCE, ±0.1)

Dimensions: 6, 6, 15MAX, 8.5, 0, 5, 12, 19, 7-φ1.2, 2-φ3.2

Dimensions: 0.3(最大) <MAX.>, 6±0.3, 6, t0.64, 3.4±0.5

	---	SELECTIVE-TIN (MATTE)	SELECTIVE GOLD (0.38μm MIN.)	NATURAL	2-5172039-1
	---	SELECTIVE-TIN (MATTE)	SELECTIVE GOLD (0.76μm MIN.)	NATURAL	1-5172039-1
OBSOLETE	12.6		PRE-TIN	NATURAL	4-172039-1
OBSOLETE	2.6		PRE-TIN	NATURAL	3-172039-1
OBSOLETE	---	TIN-LEAD	SELECTIVE GOLD (0.38μm MIN.)	GREEN	2-172039-4
OBSOLETE	---	TIN-LEAD	SELECTIVE GOLD (0.38μm MIN.)	NATURAL	2-172039-1
OBSOLETE	---	TIN-LEAD	SELECTIVE GOLD (0.76μm MIN.)	GREEN	1-172039-4
OBSOLETE	---	TIN-LEAD	SELECTIVE GOLD (0.76μm MIN.)	NATURAL	1-172039-1
OBSOLETE	---		PRE-TIN	YELLOW	172039-7
OBSOLETE	---		PRE-TIN	GRAY	172039-6
OBSOLETE	---		PRE-TIN	BLUE	172039-5
OBSOLETE	---		PRE-TIN	GREEN	172039-4
OBSOLETE	---		PRE-TIN	BROWN	172039-3
OBSOLETE	---		PRE-TIN	BLACK	172039-2
OBSOLETE	---		PRE-TIN	NATURAL	172039-1
	△ NON TAB PLACES タブなし箇所	SOLDERING SIDE 半田付け部	CONTACT SIDE 接触部側	COLOR 色	PART NUMBER 製品型番
		CONTACT FINISH コンタクト仕上			

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T.SHINOHARA	31AUG07	TE Connectivity	
DIMENSIONS: 単位: 概 mm		CHK K.BETSUI	31AUG07		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		APVD K.BETSUI	31AUG07	NAME 名称 7P HORIZONTAL TYPE CAP HOUSING ASS'Y MULTI-INTERLOCK CONN. (WIRE TO P.C.B.)	
0 ≤ x ≤ 10 : ±0.2 10 ≤ x ≤ 30 : ±0.25 30 ≤ x ≤ 100 : ±0.3 ANGLE : ±3°		PRODUCT SPEC 製品規格 SEE NOTE 5		APPLICATION SPEC 取付適用規格	
MATERIAL 材料 HSG: 66 NYLON CONTACT: BRASS		FINISH 仕上 SEE TABLE		SIZE A2	CAGE CODE 00779
		WEIGHT -		DRAWING NO 番号 C=172039	RESTRICTED TO -
		CUSTOMER DRAWING		SCALE 尺度 2:1	SHEET 1 of 1
				REV E6	

1471-9 (3/11)

Downloaded From [Oneyac.com](http://www.Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)