

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	16	C	REVISED PER ECO-11-022150	26MAR12	KH FB

57.78±0.50 [2.275±.02]
 19.18±0.50 [.755±.02]
 3.12±0.25 [.123±.010]
 24.00±0.50 [.945±.02]
 2.79±0.38 [.110±.015]
 0.63±0.20 [.025±.008]
 .71 [.028]
 3.68±0.25 [.145±.010]
 0.71 [.028]
 24.00 ±0.50 [.945 ±.02]

- 1 ZINC PER QQ-Z-363
- 2 BERYLLIUM COPPER PER QQ-C-530.
- 3 POLYMETHYLPENTENE, GENERAL PURPOSE.
- 4 NICKEL PLATE PER QQ-N-290, 3.81µm [.000150] MINIMUM THICK.
- 5 GOLD PLATE PER ASTM-B-488, 0.76µm [.000030] MINIMUM THICK.
- 6 INTERFACE PER MIL-C-39012.
- 7 BRASS PER ASTM-B-16.
- 8 TIN PLATE PER ASTM-B-545, 3.81µm [.000150] MINIMUM THICK.

DIELECTRIC 2.54 DIA [.100 DIA] 3

8 SPLIT PIN
 Ø1.78±0.05 [Ø.070±.002]
 Ø2.08±0.03 [Ø.082±.001] MAX SPLIT 2 PLACES

CONTACT 2 5

SHELL 1 4

MOUNTING POST 7 8
 Ø1.83⁰_{-0.05}
 Ø.072^{+0.000}_{-.002}
 2 PLACES

Ø0.89±0.08 [.035±.003] 2 HOLES
 1.73±0.05 [.068±.002]
 Ø2.64±0.05 [.104±.002]
 .255±0.05 [.100±.002]
 Ø2.01±0.05 [.079±.002] 4 HOLES
 2.72±0.05 [.107±.002]
 8.26±0.05 [.325±.002]
 5.44±0.05 [.214±.002]
 5.43±0.05 [.214±.002]

PCB CONFIGURATION

5.43 [.214]
 5.66 [.223]
 Ø1.27 [Ø.050] 5 PLACES
 5.26 [.207]
 6.53 [.257]
 5.44 [.214]
 10.52±0.13 [.414±.005]
 2.12 [.083]
 3.5 [.138]
 1.73±0.38 [.068±.015]

5414974-1
 PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. ALCORTA - DOCK5 27APR2005	STE TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK J. HAVENER 27APR2005		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. LIPPERT 27APR2005	NAME JACK, RIGHT ANGLE PCB, 50 OHM, SERIES BNC	
0 PLC ± -	1 PLC ± -	PRODUCT SPEC 108-12078	SIZE A2	CAGE CODE 00779
2 PLC ± 0.08 [.003]	3 PLC ± -	APPLICATION SPEC	DRAWING NO C=5414974	RESTRICTED TO -
4 PLC ± -	ANGLES ± -	WEIGHT -	SCALE 2:1	SHEET 1 of 1
MATERIAL SEE NOTES 1,2,3,7	FINISH SEE NOTES 4,5,8	CUSTOMER DRAWING	REV C	

1471-9 (3/11) Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)