

Dustproof;  
 Protection class IP 54 TO IEC 529 (EN 60 529)  
 with mounting bracket.  
 Terminals shape similar to 8092-1  
 Coil and load 6.3 x 0.8 mm  
 Integrated component: Diode

PART	MATERIAL	COLOUR
Bracket	St2	Ni plating
Cover	PA 66 GF 25	Grey sim. to RAL 7005
Base	PA 66 GF 25	Black sim. to RAL 9005
Coil Terminals 85 and 86	CuSn	Pre-tinned Sn
Load terminals 30, 87 and 87a	E-Cu	Pre-tinned Sn

OBSOLETE BOSCH P/N	TE P/N	REV	PART NUMBER	CUSTOMER P/N	CODE NO
0 332 204 212	9-1904049-3		V23134-A1007-X940		

PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.			CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD	PAPER SIZE <b>A2</b>
APPLICABLE SPEC.:			FINISH DIMENSIONS APPLY PLATING	
TOLERANCE UNLESS SPECIFIED OTHERWISE		DIMENSIONS IN MM	SCALE <b>2:1</b>	WEIGHT <b>Ca.35g</b>
DATE: 02.02.2009 NAME: L.Sandoval			PART NAME <b>POWER F RELAY          CHANGE OVER 24V BRACK</b>	
LOCATION: AMR PE EVORA			PART NO. <b>V23134-A1007-X940-CD</b>	
Tyco Electronics CLASS 3			SHT. <b>1</b> OF 2	
REV. CHANGE ORDER DATE APP.			CUSTOMER DRAWING	

Nominal voltage (load and excitation circuit) 24V

Permissible ambient temperature -40° C...+100° C

Operate voltage (at 20° C) <17.0 V

Release voltage (at 20° C) 3V...11V

Operate time <10 ms

Release time <15 ms

Contact material silver based

Equivalent coil resistance at terminal 85-86 305±15 Ohm

Voltage drop at blade terminals at a measuring current of 10A±0.5A

Normally Open Contact, Terminal 30-87,

in new condition

After life test

typ.30mV, max. 300mV

max. 300mV

Normally Closed Contact, Terminal 30-87a

in new condition

After life test

typ.50mV, max. 300mV

max. 300mV


Electrical Endurance

Resistive Load 20A on NO

Resistive Load 10A on NC

>200.000 cycles

>200.000 cycles



PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.				CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD		PAPER SIZE <b>A3</b>		
APPLICABLE SPEC.:				FINISH  DIMENSIONS APPLY      PLATING				
TOLERANCE UNLESS SPECIFIED OTHERWISE			DIMENSIONS IN MM		SCALE WEIGHT <b>Ca.35g</b>		MATERIAL	
		DATE DWN. 02.02.2009 L.Sandoval		PART NAME <b>POWER F RELAY CHANGE OVER 24V BRACK</b>				
		APP.		PART NO. <b>V23134-A1007-X940-CD</b>				
		REV.		LOCATION AMR PE EVORA		SHT. <b>2</b>		
		DATE 2009-02-02 LSan				OF 2		
REV. CHANGE ORDER		DATE		APP. CLASS 3		CUSTOMER DRAWING		

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)