

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	16	F1	REVISED PER ECO-05-013879	28NOV05	BM JGH

1 FOR USE WITH HAND TOOL 220190-1.  
 2 USE WITH MILITARY HAND TOOL M22520/5-01.  
 3 USE WITH MILITARY HAND TOOL M22520/2-01 (DANIELS AFMB) WITH DANIELS POSITIONER K1041.  
 4 SPECIAL XEROX STYLE 1275 CABLE, RG-178/U, -178A/U, -178B/U, -196/U AND -196A/U CABLES.

RECOMMENDED STRIP LENGTH  
SCALE :NTS

ISOMETRIC VIEW

4	SET AT NO 4 POSITION	Y444	58046-1 (AREA A)	414170-2
	RG-174/U, 188/U & 316/U	SET AT NO 4 POSITION	Y444	58046-1 (AREA A)
	FOR USE WITH CABLE	DANIELS POSITIONER CONTACT CRIMP 3	DANIELS DIE SET BRAID CRIMP 2	AMP DIE SET 1
				PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. WERNER 8-20-91	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK G. MICHAEL 9/25/91	NAME CONNECTOR, JACK, SERIES SMB	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± .010 3 PLC ± .005 4 PLC ± - ANGLES ± - FINISH -		APVD -	PRODUCT SPEC -	APPLICATION SPEC -
MATERIAL -	FINISH -	WEIGHT -	SIZE A2	CAGE CODE 00779
		DRAWING NO C=414170		RESTRICTED TO -
		CUSTOMER DRAWING		SCALE 8:1
		SHEET 1 of 1		REV F1

AMP 1471-9 REV 31MAR2000  
Downloaded From [Onezac.com](http://Onezac.com)

414170

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)