

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|---------------|-----------|-----|------|
| | A | INITIAL | 26JUN2015 | DW | CW |
| | B | ECR-20-008190 | 04AUG2020 | WQR | CW |
| | B1 | ECR-21-105138 | 25JUN2021 | WQR | CW |

SCALE 1:2

NOTES:

1. TECHNICAL CHARACTERISTICS:
 HOOD MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE: POWDER COATED, INSIDE AND OUTSIDE
 GREY COATING
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 上壳材料: 铝合金
 表面处理: 粉末涂层, 里外喷漆, 灰色
 防护等级: IP65(配合)

| | | | |
|-----------------|---|----------------------|-----|
| T1230160132-100 | H16B-TSH-M32 INSIDE AND OUTSIDE COATING | HIGH CONSTRUCTION | M32 |
| T1230160140-100 | H16B-TSH-M40 INSIDE AND OUTSIDE COATING | | M40 |
| PART NUMBER | DESCRIPTION | TYPE | IG1 |

| | | | | | |
|--|---|------------------|------------|--|------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN | 26JUN2015 | TE Connectivity NAME H16B-TSH-M/PG INSIDE AND OUTSIDE COATING | |
| DIMENSIONS: mm | | CHK | 26JUN2015 | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD | 26JUN2015 | | |
| 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±- FINISH ±- | | PRODUCT SPEC | 108-137013 | | |
| MATERIAL | - | APPLICATION SPEC | 114-137013 | SIZE | A3 |
| | | WEIGHT | - | CAGE CODE | 00779 |
| | | Customer Drawing | | DRAWING NO | C-T12X01601XXX00 |
| | | | | RESTRICTED TO | - |
| | | | | SCALE | 1:1 |
| | | | | SHEET | 1 OF 1 |
| | | | | REV | B1 |

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)